

# PFT M12 crimp shielded A-cod. 4pol. male



Part number	21 03 822 1425
Specification	PFT M12 crimp shielded A-cod. 4pol. male
HARTING eCatalogue	https://b2b.harting.com/21038221425

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	Circular connectors M12
Element	Cable connector Panel feed through
Specification	for rear mounting

#### Version

Termination method	Crimp termination
Gender	Male
Shielding	Shielded
Number of contacts	4
Coding	A-coding
Locking type	Screw locking
Details	Please order crimp contacts separately.

#### Technical characteristics

Conductor cross-section	0.14 0.75 mm²
Conductor cross-section	AWG 26 AWG 18
Wire outer diameter	≤2.3 mm
Rated current	4 A
Rated voltage	250 V
Rated impulse voltage	1.5 kV
Pollution degree	3

This product is not orderable anymore. Please contact your local distribution partner.



#### Technical characteristics

Overvoltage category	III
Insulation resistance	>10 <sup>8</sup> Ω
Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Limiting temperature	-40 +85 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	4.5 8.8 mm
Isolation group	I (600 ≤ CTI)

## Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel Naphthalene

#### Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079

### Commercial data

Packaging size	1
Net weight	43.8 g

Page 2 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany
Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

Product data sheet 21 03 822 1425 PFT M12 crimp shielded A-cod. 4pol. male

This product is not orderable anymore. Please contact your local distribution partner.



#### Commercial data

Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140139602
eCl@ss	27440116 Circular connector (for field assembly)