

## ix Type A - RJ45 AWG28 CAT6A PVC 0.2m



Part number	33 48 065 3830 002
Specification	ix Type A - RJ45 AWG28 CAT6A PVC 0.2m
HARTING eCatalogue	https://b2b.harting.com/33480653830002

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	System cabling
Series	HARTING ix Industrial <sup>®</sup> RJ45
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING ix Industrial <sup>®</sup> Type A Solder termination
Connector 2	RJ45 Piercing termination
Type of cable	Copper cable (round)
Version	
Cable length	0.2 m
Number of cores	8
Core structure	4x 2x AWG 28/7
Technical characteristics	
Transmission characteristics	Cat. 6 <sub>A</sub> Class E <sub>A</sub> up to 500 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s

Page 1 / 2 | Creation date 2023-08-31 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com

10 Gbit/s



## **Technical characteristics**

European customs tariff number

GTIN

ETIM

eCl@ss

Limiting temperature	-40 +70 °C
Material properties	
Material (cable)	PVC
Colour (cable)	Yellow
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Specifications and approvals	
Specifications	IEC 61076-3-124
Commercial data	
Packaging size	1
Net weight	18.36 g
Country of origin	China

85444290

EC002599

5713140264045

27060390 Ready-made data cable (unspecified)

Page 2 / 2 | Creation date 2023-08-31 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com