High Quality Power Cord UL Certificated




RoHS Compliant




-1500±50 (59"±2")-







(Wire Cross-Section)



(IEC 60320, C13, 10A 250V~) (Dimensions of Connector Face)

Dimensions: Millimetres

Plug Component				
Colour	Component			
35P (Black)	(IEC 60320, C14, 10A 250V	1		
Nickel-plated	2.0×4.0 (GEM 98672-1) (2.0×4.0 Computer Solid Blades)	3		
Black	GEM 8671P (Computer 2×4 Serial Housing)	1		

	Dimension					
Strip	ROJ	Colour				
6 +1/-0	20 ±2	Brown (L)				
6 +1/-0	20 ±2	Blue (N)				
6 +1/-0	20 ±2	Green-Yellow (E)				

Wire Styles
SJT 18AWGx3C
(CEE Cord)
60°C Black
Length: 1,500mm ±50mm
59" ±2"

Connector Component				
Instruction	Qty.	Colour		
(IEC 60320, C13, 10A 125V)	1	35p (Black)		
2.0 × 4.0 GEM 98740BS-0 (#16-18) (Receptacle Terminal)	3	Brass-Natural		
GA005-5 (2.0×4.0 Serial Housing)	1	Off-White		

Dimensions					
ROJ	Strip	Colour			
16±1	5 +1/-0	Brown (L)			
16±1	5 +1/-0	Blue (N)			
16±1	5 +1/-0	Green-Yellow (E)			

Dimensions : Millimetres

High Quality Power Cord UL Certificated



Note:

1. Hi-Pot Test: 1,500V/1Sec; <0.5mA

2. Insulation Resistance Test : DC 500/min>100m Ω

- 3. Continuity & Polarization Test: No short circuit, break circuit, displacement.
- 4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
- 5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
- 6. All material according to Non-toxic standard.



Part Number Table

Description	Part Number
C14 to C13, SJT, CEE, 18/3C, 10A 250V	PE05901US-SJT

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.

Page <2> 10/01/23 V1.0