



## 2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts

### Power Dividers Technical Data Sheet

PE20DV1058

#### Features

- 2-Way Power Divider
- High Power Wilkinson Design
- 0 to 26.5 GHz Frequency Range
- Max Power 20 Watts (CW)
- Insertion Loss < 1.2 dB
- Isolation > 16 dB

#### Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

#### Description

Pasternack carries a wide selection of power dividers to fit your needs. These components are essential in many systems, allowing the combination of multiple signals or splitting of a single signal into multiple signals with equal magnitude and phase. Pasternack's resistive and Wilkinson power dividers come with excellent performance featuring minimal loss, high isolation and low VSWR. They are available in both narrow and broad bandwidths with a variety of connector types such as 2.92mm, BNC, N and SMA.

The PE20DV1058 is a 2-way high power Wilkinson power divider that operates from 0 to 26.5 GHz and can handle up to 20 Watts (CW) with 1.2 dB max insertion loss and 16 dB min isolation. The package interface uses 2.92mm female connectors and is REACH and RoHS compliant.

#### Electrical Specifications

Design: Wilkinson  
 Number of Output Ports: 2

Description	Minimum	Typical	Maximum	Units
Frequency Range	1		26.5	GHz
Impedance		50		Ohms
Input VSWR		1.6:1	1.7:1	
Output VSWR		1.5:1	1.6:1	
Insertion Loss		0.8	1.2	dB
Isolation	16	18		dB
Amplitude Balance		±0.4	±0.5	dB
Phase Balance		±5	±6	Degrees
Input Power (CW)			20	Watts
Reverse Power (CW)			1	Watt
Input Power (Peak)			200	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts PE20DV1058](#)



2 Way 2.92mm Power Divider from 1 GHz  
to 26.5 GHz Rated at 20 Watts

## Power Dividers Technical Data Sheet

PE20DV1058

### Mechanical Specifications

#### Size

Length	3.19 in [81.03 mm]
Width	1.02 in [25.91 mm]
Height	0.39 in [9.91 mm]

Housing Material and Plating	Aluminum, Gold
------------------------------	----------------

#### Configuration

Package Type	Connectorized
Input Connector	2.92mm Female
Output Connectors	2.92mm Female

### Environmental Specifications

#### Temperature

Operating Range	-45 to +85 deg C
Storage Range	-55 to +125 deg C

Humidity	100% RH at 35°C, 95% RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts PE20DV1058](#)




2 Way 2.92mm Power Divider from 1 GHz  
to 26.5 GHz Rated at 20 Watts

Power Dividers Technical Data Sheet

PE20DV1058

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts PE20DV1058](#)



## 2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts

### Power Dividers Technical Data Sheet

PE20DV1058



2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts PE20DV1058](https://www.pasternack.com/2-way-2.92mm-power-divider-26.5-ghz-pe20dv1058-p.aspx)


URL: <https://www.pasternack.com/2-way-2.92mm-power-divider-26.5-ghz-pe20dv1058-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE20DV1058 CAD Drawing

2 Way 2.92mm Power Divider from 1 GHz to 26.5 GHz Rated at 20 Watts

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/23/19	S.PONG



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS	
TOLERANCES:	
X±.2 [5.08]	FRACTIONS ±.132
.XX±.01 [25]	ANGLES ± 1°
.XXX±.005 [1.13]	
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	
THIRD-ANGLE PROJECTION	

 <b>PASTERNAK</b> an INFINITO brand		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.
Pasternack Enterprises, Inc. P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920   1.866.727.8376 Fax: 1.949.261.7451 www.pasternack.com   e-mail: sales@pasternack.com		SHEET 1 OF 1 SCALE N/A
SIZE [CAGE] A 53919	DRAWN BY [PART NUMBER] KDANG	REV A

**LABEL:**  
**PASTERNAK**  
**PE20DV1058**  
 D/C: XXXX

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.