



Outdoor Rated N Male Right Angle to N Male  
Right Angle Low PIM Cable 200 cm Length Using  
SPO-500 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6373-200CM

### Configuration


- Connector 1: N Male Right Angle
- Connector 2: N Male Right Angle
- Cable Type: SPO-500

### Features

- Max Frequency 6 GHz
- Low PIM: -160 dBc Max
- 83% Phase Velocity
- PE Jacket
- 100% Tested with PIM Test Results Marked on Cable
- Lightweight and Extremely Flexible
- Low Loss with Excellent VSWR
- IP67 (when mated)
- Using Times Microwave Components

### Applications

- General Purpose
- Laboratory Use
- Low PIM Applications
- Distributed Antenna Systems (DAS)
- Multi-Carrier Communication Systems
- PIM Testing



### Description

Pasternack's PE3C6373-200CM type N male right angle to type N male right angle 200 cm cable using SPO-500 coax is part of our full line of RF components available for same-day shipping. Pasternack's corrugated RF cable assemblies are ideal for applications where durability and high power are needed. This Pasternack type N to type N cable assembly has a male to male gender configuration with 50 ohm corrugated SPO-500 coax. The PE3C6373-200CM type N male to type N male cable assembly operates to 6 GHz. Our low PIM design also offers excellent passive intermodulation performance with PIM levels better than -160 dBc. The right angle type N interfaces on the SPO-500 cable allow for easier connections in tight spaces. Times Microwave cable is used in each assembly and TMS components are used to form connections with the super flexible low PIM cable. These cable assemblies are expertly built to satisfy your specific need with high quality Times Microwave Systems manufactured parts.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts PE3C6373-200CM](#)



Outdoor Rated N Male Right Angle to N Male  
Right Angle Low PIM Cable 200 cm Length Using  
SPO-500 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

PE3C6373-200CM

### Electrical Specifications

| Description             | Minimum | Typical    | Maximum | Units        |
|-------------------------|---------|------------|---------|--------------|
| Frequency Range         | DC      |            | 6       | GHz          |
| VSWR                    |         |            | 1.4:1   |              |
| Velocity of Propagation |         | 83         |         | %            |
| Passive Intermodulation |         | -165       | -160    | dBc          |
| Capacitance             |         | 24 [78.74] |         | pF/ft [pF/m] |

### Specifications by Frequency

| Description           | F1   | F2   | F3   | F4   | F5 | Units |
|-----------------------|------|------|------|------|----|-------|
| Frequency             | 0.5  | 1    | 2    | 6    |    | GHz   |
| Insertion Loss (Max.) | 0.31 | 0.43 | 0.62 | 1.12 |    | dB    |

#### Electrical Specification Notes:

PIM test results vary between cables

The Insertion Loss data above is based on the performance specifications of the coax used in this assembly. The Insertion Loss includes an estimated insertion loss of  $0.1 \cdot \sqrt{FGHz}$  dB per connector.

### Mechanical Specifications

#### Cable Assembly

Length\* 78.74 in [200 cm]

#### Cable

Cable Type SPO-500  
 Impedance 50 Ohms  
 Inner Conductor Type Solid  
 Inner Conductor Material and Plating Copper Clad Aluminum  
 Dielectric Type Foam PE  
 Number of Shields 1  
 Shield Layer 1 Helically Corrugated Copper Tube  
 Outer Conductor Material and Plating Copper  
 Jacket Material PE, Black  
 Jacket Diameter 0.53 in [13.46 mm]

One Time Minimum Bend Radius 2.25 in [57.15 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts PE3C6373-200CM](#)



Outdoor Rated N Male Right Angle to N Male  
Right Angle Low PIM Cable 200 cm Length Using  
SPO-500 Coax Using Times Microwave Parts

## RF Cable Assemblies Technical Data Sheet

PE3C6373-200CM

### Connectors

| Description                   | Connector 1         | Connector 2         |
|-------------------------------|---------------------|---------------------|
| Type                          | N Male Right Angle  | N Male Right Angle  |
| Impedance                     | 50 Ohms             | 50 Ohms             |
| Contact Material and Plating  | Brass, Silver       | Brass, Silver       |
| Contact Plating Specification | 200 µin             | 200 µin             |
| Dielectric Type               | PTFE                | PTFE                |
| Body Material and Plating     | Brass, Tri-Metal    | Brass, Tri-Metal    |
| Body Plating Specification    | 80 µin              | 80 µin              |
| Torque                        | 10 in-lbs [1.13 Nm] | 10 in-lbs [1.13 Nm] |

Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8$ ", whichever is greater.

### Environmental Specifications

#### Temperature

|                 |                   |
|-----------------|-------------------|
| Operating Range | -55 to +200 deg C |
| Storage Range   | -55 to +200 deg C |

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts PE3C6373-200CM](#)



Outdoor Rated N Male Right Angle to N Male  
Right Angle Low PIM Cable 200 cm Length Using  
SPO-500 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6373-200CM

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts PE3C6373-200CM](#)



Outdoor Rated N Male Right Angle to N Male  
Right Angle Low PIM Cable 200 cm Length Using  
SPO-500 Coax Using Times Microwave Parts

RF Cable Assemblies Technical Data Sheet

PE3C6373-200CM

**How to Order**

Part Number Configuration:

**PE3C6373**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C6373-12 = 12 inches long cable  
PE3C6373-100cm = 100 cm long cable

Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable 200 cm Length Using SPO-500 Coax Using Times Microwave Parts PE3C6373-200CM](#)


URL: <https://www.pasternack.com/n-male-n-male-spo500-cable-assembly-pe3c6373-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE3C6373-200CM CAD Drawing

Outdoor Rated N Male Right Angle to N Male Right Angle Low PIM Cable  
200 cm Length Using SPO-500 Coax Using Times Microwave Parts

| REVISIONS |                 |          |
|-----------|-----------------|----------|
| REV.      | DESCRIPTION     | DATE     |
| A         | INITIAL RELEASE | 05/20/19 |
|           |                 | APPROVED |
|           |                 | S. ELLIS |



|   |   |                 |
|---|---|-----------------|
| <p>UNLESS OTHERWISE SPECIFIED<br/>LEADING DIMENSIONS ARE INCHES<br/>DIMENSIONS IN [ ] ARE MILLIMETERS</p> <p>TOLERANCES:<br/>                 X±.2 [5.08]<br/>                 .XX±.01 [ .25]<br/>                 .XXX±.005 [ .13 ]</p> <p>FRACTIONS<br/>                 ±.132<br/>                 ANGLES ± 1°</p> <p>ALL DIMENSIONS SHOWN<br/>ARE FOR REFERENCE ONLY.</p> <p>THIRD-ANGLE PROJECTION</p> | <p><b>PE PASTERNAK</b><br/>an INFINITO brand</p> <p>Pasternack Enterprises, Inc.<br/>                 P.O. Box 16759, Irvine, CA 92623.<br/>                 Phone: 1.949.261.1920   1.866.727.8376<br/>                 Fax: 1.949.261.7451<br/>                 www.pasternack.com   e-mail: sales@pasternack.com</p> | SHEET 1 OF 1    |
|   |   | SCALE N/A       |
| SIZE A  | CAGE # 53919  | DRAWN BY K.DANG |
| PART NUMBER PE3C6373  |   | REV A           |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.