



698-960 MHz / 1710-2700 MHz / 3400-4200 MHz  
 Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector

## Antennas Technical Data Sheet

PE51FP1016

### Features

- Low Passive Intermodulation (PIM) <-153 dBc @ 2x20W
- Vertical Polarization
- Low return loss, stable performance
- 4.3-10 Female connector for long lasting consistent results
- Covers 5G, WiFi and LTE frequency bands including extended CBRS

### Applications

- Indoor distribution of 5G, LTE, GSM/CDMA
- In-building public or private networks
- LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- MIMO DAS (Distributed Antenna Systems)
- Wall Mounts

### Description

The PE51FP1016 from Pasternack is a high performance, low PIM rated, wall mount panel antenna designed for in-building Distributed Antenna System (DAS) Networks. The PE51FP1016 operates from 698 to 4200 MHz which is ideal for 5G, LTE, CDMA, LPWAN/IoT/M2M applications including LoRA, LTE-M, and NB-IOT. The Multi-Band design of the Pasternack PE51FP1016 antenna eliminates the need to purchase different antennas for each frequency. The same antenna can be used for a wide array of in-building wireless applications where wide coverage is desired. Pasternack's PE51FP1016 can be used to distribute Cellular and WiFi signals throughout a building or area.

The directional 55 to 80 degree antenna with vertical polarization PE51FP1016 from Pasternack has 4.3-10 connectors and 5-8.5 dBi of gain. The key to providing the best performance in telecommunications is to ensure the components used are low PIM rated. This helps meet the increasing demand for higher data rates and the ability to provide streaming video for mobile devices. With a low PIM rating of <-150 dBc, the 698-4200 MHz PE51FP1016 helps meets the most demanding PIM requirements for 5G and LTE/4G bands.

The 4.3-10 connectorized PE51FP1016 antenna from Pasternack excels in large open areas such as indoor courtyards, indoor sporting venues, convention centers and shopping malls. The mounting bracket and hardware are included for easy installation. Our Pasternack ISO 9001:2008 registered facilities in Irvine, CA ships all 4.3-10 RF, microwave and millimeter wave waveguide components from stock the same day you purchase them. Pasternack offers the broadest and deepest in-stock inventory and is where to buy 5G antennas. Our expert technical support and friendly, knowledgeable customer service personnel are available to assist you with your particular needs for wall mount panel 5G cellular antennas.

### Configuration

Design	Panel
Band Type	Wide
Radiation Pattern	Omni Directional
Polarization	Vertical
Connector Type	4.3-10 Female
Number of Ports	1

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	698		4200	MHz
Input VSWR			1.8:1	
Impedance		50		Ohms
Gain		5	8.5	dBi

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [698-960 MHz / 1710-2700 MHz / 3400-4200 MHz Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector PE51FP1016](#)



698-960 MHz / 1710-2700 MHz / 3400-4200 MHz  
 Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall  
 Mount, 2 x 4.3-10 Female Connector

## Antennas Technical Data Sheet

PE51FP1016

Input Power	50	Watts
Passive Intermodulation 3rd Order, 2 x 20 W	-153	

### Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.698 to 0.806	0.806 to 0.96	1.71 to 2.17	2.2 to 2.7	3.4 to 4.2	GHz
Gain	5	6	7	7.5	8.5	dBi
Horizontal Beam Width	80	80	65	60	55	Degrees
Vertical Beam Width	73	70	60	60	30	Degrees

### Mechanical Specifications

Radome Material	ABS
<b>Size</b>	
Overall Length	7.09 in [180.09 mm]
Width	6.69 in [169.93 mm]
Height	2.36 in [59.94 mm]
Weight	0.88 lbs [399.16 g]

### Environmental Specifications

<b>Temperature</b>	
Operating Range	-55 to +60 deg C
Humidity	< 95

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [698-960 MHz / 1710-2700 MHz / 3400-4200 MHz Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector PE51FP1016](#)



698-960 MHz / 1710-2700 MHz / 3400-4200 MHz  
Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall  
Mount, 2 x 4.3-10 Female Connector

## Antennas Technical Data Sheet

PE51FP1016

698-960 MHz / 1710-2700 MHz / 3400-4200 MHz Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [698-960 MHz / 1710-2700 MHz / 3400-4200 MHz Low PIM Rated DAS V-pol Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector PE51FP1016](https://www.pasternack.com/698-mhz-4200-mhz-indoor-4g-5g-flat-panel-antenna-5-8.5-dbi-low-pim-4.3-10-female-connector-hg74208fpr-4310f-p.aspx)


URL: <https://www.pasternack.com/698-mhz-4200-mhz-indoor-4g-5g-flat-panel-antenna-5-8.5-dbi-low-pim-4.3-10-female-connector-hg74208fpr-4310f-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE51FP1016 CAD Drawing

698-960 MHz / 1710-2700 MHz / 3400-4200 MHz Low PIM Rated DAS V-pol  
Panel Antenna, 5-8.5 dBi, Wall Mount, 2 x 4.3-10 Female Connector

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	04/19/2021
		APPROVED
		KHIETPAS



MOUNTING BRACKET

4.3-10 FEMALE CONNECTOR

<p>THIRD-ANGLE PROJECTION</p> <p>THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.</p> <p>SHEET 1 OF 1</p> <p>SCALE N/A</p>	<p><b>PE PASTERNAK</b> an INFINITI brand</p> <p>Pasternack Enterprises, Inc. P. O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920   1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com</p>	<p>SIZE A</p>	<p>CAGE CODE 53919</p>	<p>DRAWN BY DZINN</p>	<p>ITEM NO. PE51FP1016</p>	<p>REV A</p>
		<p>UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS</p> <p>TOLERANCES:</p> <p>.X = ±.2 [5.08] FRACTIONS .XX = ±.02 [ .51] ±.1/32 .XXX = ±.005 [ .13] ANGLES ± 1°</p> <p>CABLE LENGTH (L), TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] &lt; L ≤ 60 [1524] = +2 [51] / -0 60 [1524] &lt; L ≤ 120 [3048] = +4 [102] / -0 120 [3048] &lt; L ≤ 300 [7620] = +6 [152] / -0 300 [7620] &lt; L = +5% / -0</p> <p>ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.</p>	<p>REV</p>			

NOTES:

- LABEL PER ILS-100-03 (FOR INTERNAL REFERENCE ONLY)  
LABEL LOCATION FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.