

SUMMARY

Wires

Low voltage 4



Image is for illustrative purpose only

| | |
|------------------|----------------------------------|
| Series | 1P |
| Termination type | Female solder |
| IP rating | 50 |
| AWG wire size | 30.00 - 22.00 |
| Cable Ø | 2.70 - 3.90 mm |
| Status | Active |
| Matching parts | PAG.M0.4NL.AC39N |

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | PR*: Free receptacle with cable collet |
| Keying | 1 key (alpha=0; Plug: male contact; Receptacle: female contact) |
| Housing Material | PSU (Polysulfone), black |
| Variant | N : Black collet nut |

Performance

| | |
|---------------|---------------------------|
| Configuration | 1P.M04 : 4 Low Voltage |
| Insulator | L: PEEK (UL 94 / V-0/1.5) |
| Rated Current | 8 Amps |

Specifications

| | |
|--|-------------------------------|
| Contact Type: | Solder |
| Contact Dia.: | 0.9 mm (0.0354in) |
| Bucket Dia.: | 0.8 mm (0.031in) |
| Max. Solid Conductor: | 0.34 mm ² (AWG 22) |
| Max. Stranded Conductor: | 0.34 mm ² (AWG 22) |
| R (max): | 4.5 mOhm |
| Test voltage (kV rms) Contact-contact: | 1.2 |
| Air clearance min.: | 1.2 mm |
| Creepage distance min.: | 1.2 mm |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

- Endurance (Shell): >2000 mating cycles
- Temp (min / max): -50°C / +150°C
- F ret (min): 50 N
- F ret (max): 150 N
- Steam sterilization: > 100 times (with potting on rear connection)

DRAWINGS



Dimensions







| | A | L |
|-----|------|------|
| mm. | 14 | 40 |
| in. | 0,55 | 1,57 |

RECOMMENDED BY LEMO

Tools

Cables

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

| | | | |
|--------------------|------|-------|---|
| CMN.04.T28.031PGCE | PVC | GREY |  |
| CMN.04.T28.031PGZE | | Grey |  |
| CMN.04.T28.031PNCE | PVC | Black |  |
| CMN.04.T28.031PNZE | | |  |
| CMN.04.T28.031QGC | TPR | Grey | |
| 40080 | PVC | Black | |
| 40086 | PVC | Blue | |
| 40240 | PTFE | White |  |
| 4041 | PVC | Grey |  |
| 4050 | PVC | Black |  |
| 4260 | PTFE | White |  |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.