



## 2.75W Compact Fixed Blade Charger (Australia/New Zealand)



★★★★★  
Standby Power



### Features

- Fixed Blade
- CC & CV control
- Level V Compliant
- Low Cost
- 5 Star Standby power <0.03W
- No Y Cap

### Applications

- MPEG Players
- PDA
- Personal Electronics
- Digital Camera

### Safety Approvals

- C-Tick
- SAA
- IEEE1725 Approved

### Mechanical Characteristics

- Length: 42mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)

### Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Case Color
		Min.	Max.		Line	Load	
PSM03S-050Q-3	5V	0A	0.55A	100mV	±5%		Black
PSM03S-050Q-3W	5V	0A	0.55A	100mV	±5%		White

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uF// 10uF at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the Phihong directly or visit [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications.

**INPUT:**

**AC Input Voltage Rating**  
100 to 240VAC

**AC Input Voltage Range**  
90 to 264VAC

**AC Input Current**  
0.1A(RMS) max.

**Leakage Current**  
<20uA, 264VAC/63Hz

**Input Power Saving**  
≤75mW @ 115VAC/230VAC

**OUTPUT:**

**Power**  
2.75W Maximum

**Efficiency**  
Meets Level V Efficiency Requirements  
63.7% minimum average efficiency

**Over-voltage Protection**  
8.5V

**ENVIRONMENTAL:**

**Temperature**  
Operation 0 to +40°C  
Non-operation -40 to +85°C  
Humidity 90%

**Immunity**

ESD: EN61000-4-2. Level 4  
Surge: EN61000-4-5. Level 4  
Harmonic: EN61000-3-2  
Flicker: EN61000-3-3

**Emissions**

Complies with FCC Class B  
Complies with EN55032 Class B

**Dielectric Withstand (Hi-pot) Test**

Primary to Secondary: 3000VAC

**Insulation Resistance**

Primary to Secondary: 7M ohm 500VDC

**MTBF**

200K hours minimum at 120VAC, max load  
(measured at ambient 25°C)

**DC Output Connector**

USB A  
D+ and D- pins shorted together inside the  
charger

**Dimension Diagram Unit: mm**

