

2 W

DC- 8 GHz


SMC

COAXIAL ATTENUATOR

issue
15. jul. 93

Page
1 / 1

DRAWING



General tolerances: +/- 0.5 mm

R F CHARACTERISTICS

FREQUENCY RANGE : DC - 8 GHz
 IMPEDANCE : 50 Ohms
 ATTENUATION - NOMINAL : 6 dB

FREQUENCY	DC- 4 GHz	4 - 8 GHz
V.S.W.R	<= 1.15	<= 1.30
DEVIATION (dB)	+0.4 / -0.4	+0.5 / -0.5


TEMPERATURE SENSITIVITY : 4×10^{-4} dB / dB * °C
 PEAK POWER at 25°C (1µs,1%) : 100 W
 AVERAGE POWER at 25°C : 2 W

MECHANICAL CHARACTERISTICS

CONNECTORS : SMC male/female per MIL-C 39012
 WEIGHT : < 5 g

ENVIRONMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C) : -55 , +125
 STORAGE TEMPERATURE RANGE (°C) : -55 , +125



This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary

4112-9211

QUALITY Dpt app.			
CREATION PEN : CAT			
EP : -----			
Nom : KL	15. jul. 93	New issue	HS
Date: 13. apr. 90	ISSUE	REVISIONS	NAME