



Aerosusa.com  
service@aerosusa.com  
855.393.9905

**RQB90-N**



Plastic connector, quick-type, bend 90°, NPT outer thread, integrated snap-in sleeve with sealing, high density

Material: PA plastics

Temperature:

-40°C ... +120°C

-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Color: Black

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest outer dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

Note:

Lock-nuts and sealing washers sold separately. See below for corresponding accessories.

## CERTIFICATIONS



*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103



## Technical Data Sheet

Aerosusa.com  
service@aerosusa.com  
855.393.9905

Product #	Part No.	Color	Trade Size	AD	Thread	I (in)	B (in)	C (in)	E (in)	F (in)	WS (in)	lb/100	PU
5703.013.204	5703.013.204	Black	5/16"	13	3/8"	0.33	0.79	0.47	2.22	1.57	0.83	2.9101	50 PC
5020.018.204	5020.018.204	Black	3/8"	15.8	3/8"	0.39	0.91	0.47	2.34	1.77	0.94	3.4172	50 PC
5703.015.205	5703.015.205	Black	3/8"	15.8	1/2"	0.39	0.91	0.47	2.34	1.77	0.94	3.6817	50 PC
5020.018.206	5020.018.206	Black	1/2"	21.2	1/2"	0.51	1.16	0.47	2.85	1.89	1.02	4.7840	50 PC
5020.018.214	5020.018.214	Black	3/4"	28.5	3/4"	0.67	1.46	0.51	3.44	2.46	1.26	7.5178	25 PC
5020.018.216	5020.018.216	Black	1"	34.5	1"	0.91	1.73	0.53	3.76	2.87	1.54	10.6924	10 PC
5703.042.217	5703.042.217	Black	1 1/4"	42.5	1 1/4"	1.24	2.05	0.67	4.07	3.25	1.89	15.2119	10 PC
5020.018.209	5020.018.209	Black	1 1/2"	54.5	1 1/2"	1.4	2.52	0.67	4.57	3.78	2.32	20.9218	5 PC
5703.054.238	5703.054.238	Black	1 1/2"	54.5	2"	1.79	2.52	0.61	4.8	3.78	2.76	23.0603	5 PC

*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103