S21LAC-P05MJG0-220S

series_l, type_s2




General information

| Part number | S21LAC-P05MJG0-220S | |
|-------------------|---------------------|--|
| Termination | solder | |
| Size | 1 | |
| Locking principle | push | |
| Coding | a_key | |
| Cable Diameter | cable_mini_22 | |
| Cable outlet | bend_relief | |







Contact insert description

| Number of contacts | 5 |
|----------------------|--------|
| Contact type | pins |
| Contact diameter | 09mm |
| Insulator material | peek |
| Wire cross section | 22_awg |
| Termination | solder |
| Termination diameter | 085mm |

 $reverse_gender_on_request$

Technical information

| Max. creepage and air clearance distance | 09 __ mm | 12 __ mm |
|--|--------------------|--------------------|
| Nominal current single contact | 075_a | iec_60512_5_2 |
| Nominal current insert | 5,625 A | vde_0298_4 |
| Test voltage | 135_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip50 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated_unmated

Material and surface treatments

| Housing | m_chrome |
|---------|---------------|
| Contact | cu_alloy_gold |

safety_text_2 ul_text illustrative_text