| MALLORY Mallory Sonalert Products,Inc. | | Part #: | SBT12M0FL |
|--|---|--|---|
| | outline Drawing | Revision: | F |
| Specifications: | cUL Recognized as capable of me | eting Medical Sr | nec IFC60601-1-8 AMD2:2020 |
| Sound Level Category: | COL RECOGNIZED DE CAPADIC OF INC | Loud | 700 12 00 000 1 1 0 AMB2.2020 |
| Mode of Operation: | Continuous | | |
| Voltage Rating: | 9 to 12 VDC | | |
| Frequency: | 150 to 4000 Hz | | |
| Loudness @ 10cm: | 85 to 95 dB(A) Typ. | | |
| Average Current Draw: | <25mA Typ. | | |
| Ipk Current*: | 75mA | | |
| Housing Material: | ABS 777D Plastic Resin, Black | | |
| Storage Temperature: | -40° to +85° C | | |
| Operating Temperature: | -30° to +65° C | | |
| Weight Typical: | 0.6 oz (17g) | | |
| Options: Inches (mr | | se contact factory. | ROHS Compliant |
| | Ø1.750 [Ø44.5] 2.146 [54.5] Ø0.138 [Ø3.50] 2 places | | Manuary Medical |
| | 2.538 [64.5] | FLEX. S CONTR 24 AW APPRO BLACK RED W | STRANDED OL WIRES G INSULATED X. 6" LONG WIRE (-) IRE (+) |

*lpk = Instantaneous Peak

tolerances:

±0.01 [±0.3]

±0.005 [±0.1]