



Autonomous Alarm Notification

SCADADroid R2A+



Full Feature Capability

✓	Integrates with existing SCADA communications
✓	Remote access via VPN, MQTT and ReST
✓	Notify with onboard DI's and/or as ModbusTCP Master*
✓	Notifications with Text, Email and Voice (VoLTE)*
✓	Browser based configuration on smartphone, tablet, or PC
✓	Smartphone app for Android and iOS
✓	Unlimited phone/address book and shift schedule integration
✓	8 on board Discrete Inputs, 1 Discrete Output
✓	2 Analog Inputs (0-20 mA, 4-20 mA, 0-10/20/30V)
✓	Reporting function (CSV, PDF, and JSON formatting)

*optional

Applications



Water & Wastewater



Oil & Gas



Utilities



Technical Specification

DC INPUT RANGE	12-30 Volt DC	
AREA CLASSIFICATION	Class I, Div 2 cULus E515728	
PHYSICAL	Housing: Anodized Aluminum Dimensions: 4.06"/10.3cm (D) x 2.57"/6.5cm (W) x 2.69"/6.8cm (H) Weight: 12.9oz / 366g Input Connector: 8 Position Terminal Block Plug, Female Sockets 0.138" (3.50mm)	
A MOUNTING	Standard 35 mm DIN Rail mounting 00 Rear Mounted: HORIZONTAL RADIAL (Standard)	
B TEMPERATURE	- 40°F/-40°C TO 140°F/60°C	
C ANTENNA	1x Standard 50 mm GSM Antenna (Included) Connector: SMA Female	
D CELLULAR MODEM	04 LTE with VoLTE LTE Bands: B2(1900), B4 (1700), B5 (850), B12/B13/B14 (700), B66 (AWS-3), B71 (600) UMTS/HSPA+ Bands: B2 (1900), B4 (1700), B5 (850) * All Modems Accept Standard SIM Cards (Type 2FF - 15 x 25mm)	F I/O INTERFACE
E VPN	00 Open source VPN standard Consult Reonix for other VPN Options	G SOFTWARE
		H PROTOCOLS
		<p>1x RJ45 - 10/100M Ethernet 8x Digital Inputs - Dry contact or 30 VDC Max (push-pull) 1x Relay Output - 1 N/O SPST 2x Analog Inputs - Software Selectable 0-20mA, 4-20mA, 0-10V, 0-20V, 0-30V 10x LED Indicators: 8 DI Status, 1 Power Status, 1 System Status</p> <p>Reonix Web Interface: Easy to use, Secure Utilized for initial SCADADroid® setup, programming of Alarms, Phonebook, Shift Schedules, VPN and much more.</p> <p>01 Modbus TCP/IP: Interface with PLC/RTU/HMI</p> <p>MQTT: Publisher/Subscriber protocol for M2M, minimizing data usage REST: Architecture providing standards between networked systems on web</p>

Ordering Requirements

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box.

ORDERING EXAMPLE: R2-0000-0000-0000

