

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Halogen Free. "Green" Device (Note 2)
- For Surface Mount Applications
- Extremely Low Thermal Resistance
- · Easy Pick And Place
- High Current Capability With Low Forward Voltage
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +175°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 70°C/W Junction to Ambient
- Thermal Resistance: 25°C/W Junction to Lead
- Thermal Resistance: 15°C/W Junction to Case

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	iviaximum	Maximum DC Blocking Voltage
SK3150A-L	SK3150A	150V	105V	150V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	3.0A	T _L =120°C
Peak Forward Surge Current	I _{FSM}	80A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage	V _F	0.86V	I _{FM} =3.0A; T _J =25°C*
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	0.01mA 1.0mA	T _J =25°C T _J =100°C
Typical Junction Capacitance	CJ	100pF	Measured at 1.0MHz, V _R =4.0V


^{*}Pulse test: Pulse width 200 µsec, Duty cycle 2%

Note:

- 1. High Temperature Solder Exemption Applied, See EU Directive Annex 7a.
- 2. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


3 Amp Schottky Rectifier 150 Volts

SMA (DO-214AC)



DIMENSIONS								
DIM	INCHES		MM		NOTE			
DIIVI	MIN	MAX	MIN	MAX	NOTE			
Α	0.075	0.096	1.90	2.44				
В	0.050	0.064	1.27	1.63				
С	0.002	0.008	0.051	0.203				
D		0.020		0.51				
E	0.030	0.060	0.76	1.52				
F	0.065	0.091	1.65	2.32				
G	0.189	0.220	4.80	5.59				
Н	0.157	0.187	4.00	4.75				
J	0.090	0.115	2.25	2.92				

SUGGESTED SOLDER PAD LAYOUT





Curve Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge

Current

80

80


8.3 ms Single Half Sine-Wave

20

1 10 100

Number of Cycles at 60 Hz

Fig. 4 - Typical Reverse Leakage Characteristics





Ordering Information

Device	Packing	
SK3150A-LTP	Tape&Reel: 5Kpcs/Reel	

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.