



4 Type

- N With plastic pad
- E With rubber pad

Inch table

Dimensions in: inches - millimeters

1 d_1		2 d_2	3 l_1	l_2	l_3	l_4	A/F
Type N	Type E	Thread					
1.00 25.4	-	1/4 x 20*	1.00 25.4	0.46 11.7	0.375 9.5	0.15 3.8	-
1.00 25.4	-	5/16 x 18*	1.00 25.4	0.46 11.7	0.375 9.5	0.15 3.8	-
1.38 35.1	-	5/16 x 18*	1.00 25.4	0.60 15.2	0.520 13.2	0.15 3.8	-
1.38 35.1	1.38 35.1	3/8 x 16	1.50 38.1	0.68 17.3	0.520 13.2	0.15 3.8	0.51 13.0
1.69 42.9	-	3/8 x 16	1.50 38.1	0.68 17.3	0.560 14.2	0.15 3.8	0.51 13.0
1.69 42.9	1.38 35.1	1/2 x 13	2.50 63.5	0.72 18.3	0.560 14.2	0.15 3.8	0.61 15.5

* No hex included

Specification

- Base
Steel, zinc plated shell
- Threaded stud
Steel
- Zinc plated, blue passivated
- With adjusting hex nut at base
- Type N
Plastic pad
Nylon, rigid
- Type E
Rubber pad
Elastomer, non-skid
- [Elastomer Characteristics](#) → page 2135
- [Plastic Characteristics](#) → page 2135
- [RoHS compliant](#)

Information

These economical SN 946 willi glide leveling mounts are designed for light duty applications. They are commonly used on office partitions, shelving, exercise equipment, point of purchase (POP) displays and smaller machines.

see also...

- [Rattle Mounts SN 974 \(with Optional Slot\)](#) → page 1500
- [Hex Leveler Bolts SN 949](#) → page 1499

How to order	
1 Base diameter d_1	
2 Thread d_2	
3 Stud length l_1	
4 Type	

SN 946-1.00-1/4X20-1.00-N