

T.440+a

Plugs

with flat dipstick, technopolymer

BSP

RoHS

PA

+212 °F
-22 °F

MATERIAL

Polyamide based (PA) technopolymer, black colour, matte finish.

PACKING RING

NBR synthetic rubber.

FLAT DIPSTICK

Flat section phosphatised steel.

On request and for sufficient quantities dipstick can be supplied in different lengths and/or complete with MAX-MIN level lines.

MAXIMUM CONTINUOUS WORKING TEMPERATURE

100°C.

SPECIAL EXECUTIONS ON REQUEST

Words, marks and graphic symbols can be tampoprinted on the cap.



ELESA Original design



Accessories for hydraulic systems

BSP

METRIC

| Code | Description | d | h | D | L | a | ⚖ |
|--------|-------------|--------|----|------|------|-----|----|
| 157211 | T.440-1/4+a | G 1/4 | 9 | 20.5 | 19 | 192 | 30 |
| 157221 | T.440-3/8+a | G 3/8 | 9 | 25 | 21 | 192 | 32 |
| 157231 | T.440-1/2+a | G 1/2 | 11 | 28.5 | 25 | 189 | 42 |
| 157241 | T.440-3/4+a | G 3/4 | 12 | 34.5 | 27 | 188 | 50 |
| 157251 | T.440-1+a | G 1 | 13 | 42.5 | 28.5 | 188 | 56 |
| 157261 | T.440-1¼+a | G1 1/4 | 13 | 52 | 32 | 185 | 72 |
| 157271 | T.440-1½+a | G1 1/2 | 13 | 57.5 | 34 | 185 | 83 |