


## FR4 PCB BASED SMD CMOS VCXO (14.3 x 8.7 x 5.0mm)

### FEATURES:


- 5G BASE STATION
- PERSONAL RADIO BASE STATION
- ULTRA LOW NOISE AND JITTER PERFORMANCE




### SPECIFICATION

PARAMETER	MIN.	TYP.	MAX.	UNIT	NOTE	
FREQUENCY		122.880		MHz		
OPERATING TEMPERATURE RANGE	-40		85	°C		
STORAGE TEMPERATURE RANGE	-55		105	°C		
SUPPLY VOLTAGE	3.135	3.3	3.435	V		
SUPPLY CURRENT		22	30	mA		
OUTPUT	LOGIC FAMILY	HCMOS				
	LOAD	15pF				
	LEVEL LOGIC '1' (V <sub>OH</sub> )	0.9 x V <sub>DD</sub>		V		
	LEVEL LOGIC '0' (V <sub>OL</sub> )		0.1 x V <sub>DD</sub>	V		
	SYMMETRY (DUTY CYCLE)	45		55	%	
	RISE AND FALL TIME (Tr/Tf)			3	nS	@ 10% ~ 90% V <sub>DD</sub>
	START-UP TIME			10	mS	
FREQUENCY DEVIATION	±20			ppm	@ APR (Inclusive of tolerance@25°C, stability over temp, voltage chance, load change and aging)	
CONTROL VOLTAGE	0		3.3	V		
AGING @ 25°C + 3°C			±3.0	ppm	@ 1 <sup>ST</sup> year	
PHASE JITTER		51		fS	@ 12kHz ~ 20MHz offset	


### PACKAGE DIMENSIONS



### PHASE NOISE (TYPICAL) @ 122.88MHz




### SOLDER PATTERN



\*0.01µF to 0.1µF bypass capacitor recommended

### REFLOW PROFILE



Note: Consult factory for detail

Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.