

UBX-M8230-CT




Super low power u-blox M8 GNSS chip

Ideal for portable applications thanks to Super-E mode

- Super-E mode: ideal balance between low power and good performance
- Optimized for portable & wrist-worn applications
- System power optimization: LNA power saving and data batching
- Concurrent reception of GPS, GLONASS, BeiDou in Super-E mode
- Minimal board space: less than 30 mm²



2.99 × 3.21 × 0.36 mm



Product description

The UBX-M8230-CT is an ultra low power GNSS chip optimized for wearable and portable applications. It features Super-E mode (Super-Efficient), providing a unique balance between power and performance. Compared with u-blox 1 Hz full power mode, the Super-E mode provides up to 3 times the power savings while maintaining good position and speed accuracy. Average power consumption over a typical 30-minute track can be lower than 20 mW, while instantaneous tracking power is less than 10 mW. This is true even when using an industrial antenna design with moderate-to-low signal levels.

Super-E has a default performance setting for the best balance between power vs. performance. It also has a power save setting for additional power savings with potential compromise on performance.

The UBX-M8230-CT optimizes the overall system power consumption by excluding the need for any heavy signal processing on the application processor, and with external components, such as an external LNA, that can be automatically duty cycled. Navigation data can be stored internally while the application processor is in deep sleep (data batching).

Used in combination with multi-GNSS Assistance data, the UBX-M8230-CT features faster Time-to-First-Fix and ensures minimal power consumption.

The UBX-M8230-CT only needs a few external components (e.g. SAW/LNA) to form a full GNSS solution with a footprint as small as 30 mm². It offers easy access to navigation data via multiple interfaces, such as SPI, I2C and UART.

The UBX-M8230-CT chip is an ideal choice for most wearable applications, such as watches, sport trackers and other applications where low power consumption and small size are key.

The UBX-M8230-CT is built on the u-blox M8 concurrent engine and supports two constellations simultaneously in Super-E mode, thus increasing the number of visible satellites compared to single-GNSS solutions. It also supports message integrity protection, anti-jamming, and anti-spoofing, providing reliable positioning in difficult environmental conditions as well as in security attack scenarios.

The UBX-M8230-CT chip is fully tested and qualified according to the JESD47 standard.

UBX-M8230-CT

Grade	
Automotive	
Professional	
Standard	•
GNSS	
GPS / QZSS	•
GLONASS	•
Galileo	cm
BeiDou	•
Number of concurrent GNSS	3
Interfaces	
UART	1
USB	
SPI	1
DDC (I ² C compliant)	1
Features	
Data logging	S
Data batching	•
RTC crystal	S
Oscillator	T

cm = only supported in continuous mode
S = supported, may require ext. components

T = TCXO supported



Features

Receiver type	72-channel u-blox M8 engine GPS/QZSS L1 C/A, GLONASS L1OF BeiDou B1I, Galileo E1B/C 1 SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN	
Time to first fix		
Cold starts:	26 s	
Aided start:	2 s	
Hot start:	1 s	
	Super-E mode (default)	Continuous mode
Sensitivity ²		
Tracking & Nav:	-160 dBm	-167 dBm
Reacquisition:	-160 dBm	-160 dBm
Cold start:	-148 dBm	-148 dBm
Hot start:	-157 dBm	-157 dBm
Max nav. update rate		
Single GNSS	Up to 4 Hz	up to 18 Hz
2 Concurrent GNSS	Up to 4 Hz	up to 10 Hz
Horizontal Pos.	3.5 m CEP	2.5 m CEP
Accuracy		
Multi-GNSS Assistance	AssistNow GNSS Online AssistNow GNSS Offline (up to 35 days) AssistNow Autonomous (up to 6 days) OMA SUPL & 3GPP compliant	
Oscillator	Supports TCXO	
Real Time Clock (RTC)	Can be derived from external RTC Clock	
LNA	Built-in	
DC/DC converter	Built-in, external component required	
Super-E mode	Super Efficient mode for lowest power	
Anti Jamming	Active CW detection and removal	
SQL Flash (optional)	For AssistNow Offline, AssitNow Autonomous, long term logging	
Raw Data	Code phase output	
Odometer	Integrated in navigation filter	
Geofencing	Up to 4 circular areas GPIO for waking up external CPU	
Spoofing detection	Built-in	
Signal integrity	Signature feature with SHA 256	
Data logging ³ and Data batching	For position, velocity, time, and odometer data	

1 Galileo only supported in continuous mode

2 GPS+GLONASS

3 External Flash required

Interfaces

Serial interfaces	1 UART 1 DDC (I ² C compliant) 1 SPI
Digital I/O	1 EXTINT interrupt inputs
Memory	SQL interface for optional Flash

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Package

UBX-M8230-CT: 47 Pin WL-CSP: 2.99 x 3.21 x 0.36 mm

Environmental data, quality & reliability

Operating temp.	-40 °C to +85 °C
Humidity	JEDEC MSL 1
RoHS compliant (lead-free) and green (no halogens)	
Qualification according to JESD47	

Electrical data

Supply voltage	1.4 V to 3.6 V
Digital I/O voltage level	1.65 V to 3.6 V
Power consumption ⁴	36 mA @ 1.4 V (continuous mode, 1 Hz) 6 mA @ 1.4 V (Super-E mode, performance setting, 1 Hz) 4.8 mA @ 1.4 V (Super-E mode, power save setting, 1 Hz)
Backup Supply	1.4 V to 3.6 V

4 = Tracking, 2 concurrent GNSS

Support products

u-blox M8 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox M8 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-M8230	u-blox M8 low power GNSS evaluation kit, supports UBX-M8230-CT chip
-----------	---

Product variants

UBX-M8230-CT	u-blox M8 low power concurrent GNSS chip, 47 pin WL-CSP
--------------	---

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2018, u-blox AG