



**Metric table**

Dimensions in: millimeters - inches

| <sup>1</sup> d <sub>1</sub> | <sup>2</sup> d <sub>2</sub><br>Thread | <sup>3</sup> Length l |            |            |            | d <sub>3</sub> | h <sub>1</sub> | h <sub>2</sub> |            |           |
|-----------------------------|---------------------------------------|-----------------------|------------|------------|------------|----------------|----------------|----------------|------------|-----------|
| 25<br>.98                   | M 4                                   | 10<br>.39             | 15<br>.59  | -          | -          | -              | -              | 13<br>.51      | 17<br>.67  | 8<br>.31  |
| 25<br>.98                   | M 5                                   | 15<br>.59             | 25<br>.98  | -          | -          | -              | -              | 13<br>.51      | 17<br>.67  | 8<br>.31  |
| 25<br>.98                   | M 6                                   | 10<br>.39             | 15<br>.59  | 20<br>.79  | 25<br>.98  | -              | -              | 13<br>.51      | 17<br>.67  | 8<br>.31  |
| 35<br>1.38                  | M 6                                   | 10<br>.39             | 15<br>.59  | 20<br>.79  | 25<br>.98  | 35<br>1.38     | -              | 18<br>.71      | 20<br>.79  | 8<br>.31  |
| 35<br>1.38                  | M 8                                   | 15<br>.59             | 20<br>.79  | 25<br>.98  | 35<br>1.38 | 40<br>1.57     | -              | 18<br>.71      | 20<br>.79  | 8<br>.31  |
| 35<br>1.38                  | M 10                                  | 25<br>.98             | 30<br>1.18 | -          | -          | -              | -              | 18<br>.71      | 20<br>.79  | 8<br>.31  |
| 45<br>1.77                  | M 6                                   | 55<br>2.17            | -          | -          | -          | -              | -              | 22<br>.87      | 26<br>1.02 | 12<br>.47 |
| 45<br>1.77                  | M 8                                   | 15<br>.59             | 20<br>.79  | 25<br>.98  | 30<br>1.18 | 35<br>1.38     | 40<br>1.57     | 22<br>.87      | 26<br>1.02 | 12<br>.47 |
| 45<br>1.77                  | M 10                                  | 20<br>.79             | 30<br>1.18 | 35<br>1.38 | 40<br>1.57 | -              | -              | 22<br>.87      | 26<br>1.02 | 12<br>.47 |
| 55<br>2.17                  | M 8                                   | 15<br>.59             | 20<br>.79  | 30<br>1.18 | 40<br>1.57 | -              | -              | 25<br>.98      | 29<br>1.14 | 15<br>.59 |
| 55<br>2.17                  | M 10                                  | 15<br>.59             | 20<br>.79  | 30<br>1.18 | 40<br>1.57 | -              | -              | 25<br>.98      | 29<br>1.14 | 15<br>.59 |
| 55<br>2.17                  | M 12                                  | 30<br>1.18            | 40<br>1.57 | -          | -          | -              | -              | 25<br>.98      | 29<br>1.14 | 15<br>.59 |

**Specification**

- Eight lobed knob  
Nylon plastic
  - Temperature resistant up to 230 °F (110 °C)
  - Glass filled
  - Black, matte finish
- Threaded stud  
Steel
  - Zinc plated
  - Molded-in
- RoHS compliant

**Information**

VPA is an economical but durable eight lobed knob for many applications.

|  |   |
|--|---|
| <p>How to order</p> <p><sup>1</sup> <sup>2</sup> <sup>3</sup></p> <p><b>VPA-35-M8-20</b></p> | <b>1</b> Handle diameter d <sub>1</sub> |
|  | <b>2</b> Thread d <sub>2</sub>          |
|  | <b>3</b> Length l                       |