


PTAC240502FC

Thermally-Enhanced High Power RF LDMOS FET
50 W, 28 V, 2300 – 2400 MHz

Description


The PTAC240502FC is a 47-watt LDMOS FET with an asymmetrical design intended for use in multi-standard cellular power amplifier applications in the 2300 to 2400 MHz frequency band. Features include dual-path design, input matching, high gain and thermally-enhanced package with earless flanges. Manufactured with Wolfspeed's advanced LDMOS process, this device provides excellent thermal performance and superior reliability.

PTAC240502FC
Package H-37248-4



Features

- Input matched
- Asymmetric Doherty design
 - Main: P1dB = 17 W Typ
 - Peak: P1dB = 33 W Typ
- Typical Pulsed CW performance, 2350 MHz, 28 V, 160 μ s pulse width, 10% duty cycle, Doherty Configuration
 - Output power at P1dB = 45.7 W
 - Efficiency = 46.2%
 - Gain = 14.6 dB
- Typical single-carrier WCDMA performance, 2350 MHz, 28 V, 8.4 dB PAR @ 0.01% CCDF
 - Output power = 8.91 W
 - Efficiency = 44.2%
 - Gain = 14.2 dB
 - ACPR = -31 dBc @ 5 MHz
- Capable of handling 10:1 VSWR @28 V, 50 W (CW) output power
- Integrated ESD protection : Human Body Model, Class 1B (per JESD22-A114)
- Low thermal resistance
- Pb-free and RoHS compliant



RF Characteristics

Two-carrier WCDMA Specifications (tested in Wolfspeed Doherty test fixture)

$V_{DD} = 28$ V, $I_{DQ} = 120$ mA, $P_{OUT} = 10$ W avg, $V_{GS1} = 1.3$ V, $f_1 = 2345$ MHz, $f_2 = 2355$ MHz, 3GPP signal, channel bandwidth = 3.84 MHz, peak/average = 8 dB @ 0.01% CCDF

Characteristic	Symbol	Min	Typ	Max	Unit
Linear Gain	G_{ps}	13	14.3	—	dB
Drain Efficiency	η_D	41	44	—	%
Intermodulation Distortion	IMD	—	-33	-25	dBc

All published data at $T_{CASE} = 25^\circ\text{C}$ unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!

DC Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_{DS} = 10\text{ mA}$	$V_{(BR)DSS}$	65	—	—	V
Drain Leakage Current	$V_{DS} = 28\text{ V}, V_{GS} = 0\text{ V}$	I_{DSS}	—	—	1	μA
	$V_{DS} = 63\text{ V}, V_{GS} = 0\text{ V}$	I_{DSS}	—	—	10	μA
On-State Resistance (main)	$V_{GS} = 10\text{ V}, V_{DS} = 0.1\text{ V}$	$R_{DS(on)}$	—	0.4	—	Ω
	(peak) $V_{GS} = 10\text{ V}, V_{DS} = 0.1\text{ V}$	$R_{DS(on)}$	—	0.2	—	Ω
Operating Gate Voltage (main)	$V_{DS} = 28\text{ V}, I_{DQ} = 120\text{ mA}$	V_{GS}	2.6	2.7	2.8	V
	(peak) $V_{DS} = 28\text{ V}, I_{DQ} = 0\text{ mA}$	V_{GS}	1.2	1.3	1.5	V
Gate Leakage Current	$V_{GS} = 10\text{ V}, V_{DS} = 0\text{ V}$	I_{GSS}	—	—	1	μA





Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	65	V
Gate-Source Voltage	V_{GS}	-6 to +10	V
Operating Voltage	V_{DD}	0 to +32	V
Junction Temperature	T_J	225	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-65 to +150	$^{\circ}\text{C}$
Thermal Resistance ($T_{CASE} = 60^{\circ}\text{C}, 50\text{ W CW}$)	$R_{\theta JC}$	1.29	$^{\circ}\text{C/W}$

Ordering Information


Type and Version	Order Code	Package Description	Shipping
PTAC240502FC V1 R0	PTAC240502FC-V1-R0	H-37248-4, earless flange	Tape & Reel, 50 pcs
PTAC240502FC V1 R250	PTAC240502FC-V1-R250	H-37248-4, earless flange	Tape & Reel, 250 pcs

Typical Performance (data taken in a production test fixture)





Typical Performance (cont.)



Load Pull Performance


Main Side Load Pull Performance – Pulsed CW signal: 160 μ s, 10% duty cycle, 28 V, 114 mA

Freq [MHz]	Zs [Ω]	P _{1dB}										
		Max Output Power					Max PAE					
		Zl [Ω]	Gain [dB]	P _{OUT} [dBm]	P _{OUT} [W]	PAE [%]	Zl [Ω]	Gain [dB]	P _{OUT} [dBm]	P _{OUT} [W]	PAE [%]	
2300	10-j31	9.4-j11.6	20.96	42.89	19.45	53.2	4.7-j8.3	22.8	41.03	12.68	61.5	
2350	12.7-j35	9.7-j12.2	20.7	42.83	19.19	52.7	5.1-j9.4	22.4	41.34	13.61	62.1	
2400	16.2-j38	9.31-j12.6	20.8	42.65	18.41	52.6	5.2-j10.2	22.2	41.45	13.96	61.3	

Peak Side Load Pull Performance – Pulsed CW signal: 160 μ s, 10% duty cycle, 28 V, 252 mA

Freq [MHz]	Zs [Ω]	P _{1dB}										
		Max Output Power					Max PAE					
		Zl [Ω]	Gain [dB]	P _{OUT} [dBm]	P _{OUT} [W]	PAE [%]	Zl [Ω]	Gain [dB]	P _{OUT} [dBm]	P _{OUT} [W]	PAE [%]	
2300	5.6-j22	3.0-j7.0	18.2	46.50	44.67	52.1	2.2-j5.8	20.5	45.20	33.11	56.9	
2350	6.7-j25	2.9-j7.9	17.4	46.46	44.26	48.5	2.2-j5.9	21.1	44.91	30.97	55.9	
2400	9.7-j29	3.3-j7.9	17.9	46.62	45.92	49.6	2.2-j6.2	20.8	45.31	33.96	57.2	

Reference Circuit , 2300 – 2400 MHz



Reference circuit assembly diagram (not to scale)


Reference Circuit (cont.)**Reference Circuit Assembly**

DUT	PTAC240502FC V1
Test Fixture Part No.	LTA/PTAC240502FC-V1
PCB	Rogers 4350, 0.508 mm [0.020"] thick, 2 oz. copper, $\epsilon_r = 3.66$, $f = 2300 - 2400$ MHz

Find Gerber files for this test fixture on the Wolfspeed Web site at www.wolfspeed.com/RF


Components Information

Component	Description	Suggested Manufacturer	P/N
Input			
C101, C105	Capacitor, 4.7 μ F	Murata Electronics North America	GRM32ER71H475KA88L
C102, C103, C104, C106	Capacitor, 18 pF	ATC	ATC800A180JT250T
R101, R102	Resistor, 10 Ω	Panasonic Electronic Components	ERJ-8GEYJ100V
R103	Resistor, 50 Ω	Anaren	060120A15Z50
R104	Resistor, 300 Ω	Venkel	CR0603-16W-3010FB
R105	Resistor, 12.1 Ω	Venkel	CR0603-16W-12R1FB
U1	Directional coupler	Anaren	X3C25P1-05S
Output			
C201, C202, C203, C204, C206, C208	Capacitor, 18 pF	ATC	ATC800A180JT250T
C205	Capacitor, 0.5 pF	ATC	ATC800A180JT250T
C207, C210, C214	Capacitor, 4.71 μ F	Murata Electronics North America	GRM32ER71H475KA88L
C209, C212	Capacitor, 10 μ F	Taiyo Yuden	UMK325C7106MM-T
C211, C213	Capacitor, 100 μ F	Panasonic Electronic Components	EEE-FP1V101AP

Pinout Diagram (top view)

Lead connections for PTAC240502FC

Package Outline Specifications



**For more information, please contact:**

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/RF

Sales Contact
RFSales@wolfspeed.com

RF Product Marketing Contact
RFMarketing@wolfspeed.com

discontinued product

Notes & Disclaimer

Specifications are subject to change without notice. “Typical” parameters are the average values expected by Wolfspeed in large quantities and are provided for information purposes only. Wolfspeed products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

© 2023 Wolfspeed, Inc. All rights reserved. Wolfspeed® and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
PATENT: <https://www.wolfspeed.com/legal/patents>

The information in this document is subject to change without notice.