



# PXAC210552FC

## Thermally-Enhanced High Power RF LDMOS FET 55 W, 28 V, 1805 – 2170 MHz

### Description

The PXAC210552FC is a 55-watt LDMOS FET with an asymmetric design for use in multi-standard cellular power amplifier applications in the 1805 to 2170 MHz frequency band. It features dual-path design, input and output matching, and a thermally-enhanced package with earless flange. Manufactured with Wolfspeed's advanced LDMOS process, this device provides excellent thermal performance and superior reliability.

PXAC210552FC  
Package H-37248-4



### Features

- Broadband internal matching
- Asymmetric Doherty design
  - Main: P1dB = 20 W Typ
  - Peak: P1dB = 35 W Typ
- CW performance, 2170 MHz, 26 V
  - Output power at P<sub>1dB</sub> = 27 W
  - Gain = 17 dB
  - Efficiency = 59%
- Integrated ESD protection
- ESD: Human Body Model, Class 1B (per ANSI/ESDA/JEDEC JS-001)
- Capable of handling 10:1 VSWR @28 V, 55 W (CW) output power
- Low thermal resistance
- Pb-free and RoHS compliant

### RF Characteristics

#### Single-carrier WCDMA Specifications (tested in Wolfspeed Doherty test fixture)

$V_{DD} = 26\text{ V}$ ,  $V_{GS(peak)} = 1.5\text{ V}$ ,  $I_{DQ} = 120\text{ mA}$ ,  $P_{OUT} = 39\text{ dBm}$  average,  $f = 2170\text{ MHz}$ . 3GPP WCDMA signal: 3.84 MHz bandwidth, 10 dB PAR @0.01% CCDF.

Characteristic	Symbol	Min	Typ	Max	Unit
Linear Gain	$G_{ps}$	16	17.2	—	dB
Drain Efficiency	$\eta_D$	46	49	—	%
Adjacent Channel Power Ratio	ACPR	—	-29	-25	dBc

All published data at  $T_{CASE} = 25^\circ\text{C}$  unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!

## DC Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_{DS} = 10\text{ mA}$	$V_{(BR)DSS}$	65	—	—	V
Drain Leakage Current (main and peak)	$V_{DS} = 28\text{ V}, V_{GS} = 0\text{ V}$	$I_{DSS}$	—	—	0.1	$\mu\text{A}$
	$V_{DS} = 63\text{ V}, V_{GS} = 0\text{ V}$	$I_{DSS}$	—	—	1.0	$\mu\text{A}$
Gate Leakage Current	$V_{GS} = 10\text{ V}, V_{DS} = 0\text{ V}$	$I_{GSS}$	—	—	0.1	$\mu\text{A}$
On-state Resistance	(main) $V_{GS} = 10\text{ V}, V_{DS} = 0.1\text{ V}$	$R_{DS(on)}$	—	0.38	—	$\Omega$
	(peak) $V_{GS} = 10\text{ V}, V_{DS} = 0.1\text{ V}$	$R_{DS(on)}$	—	0.19	—	$\Omega$
Operating Gate Voltage	(main) $V_{DS} = 26\text{ V}, I_{DQ} = 120\text{ mA}$	$V_{GS}$	2.16	2.65	3.15	V
	(peak) $V_{DS} = 26\text{ V}, I_{DQ} = 0\text{ mA}$	$V_{GS}$	1.00	1.50	2.00	V





## Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source Voltage	$V_{DSS}$	65	V
Gate-source Voltage	$V_{GS}$	-6 to +10	V
Operating Voltage	$V_{DD}$	0 to +32	V
Junction Temperature	$T_J$	225	$^{\circ}\text{C}$
Storage Temperature Range	$T_{STG}$	-65 to +150	$^{\circ}\text{C}$
Thermal Resistance ( $T_{CASE} = 70^{\circ}\text{C}, 26\text{ V}, 8\text{ W CW}$ )	$R_{\theta JC}$	1.44	$^{\circ}\text{C/W}$





## Ordering Information

Type and Version	Order Code	Package and Description	Shipping
PXAC210552FC V1 R0	PXAC210552FC-V1-R0	H-37248-4, ceramic open-cavity, earless	Tape & Reel, 50 pcs
PXAC210552FC V1 R2	PXAC210552FC-V1-R2	H-37248-4, ceramic open-cavity, earless	Tape & Reel, 250 pcs

**Typical Performance** (data taken in Wolfspeed Doherty reference test fixture)





Typical Performance (cont.)





**Typical Performance (cont.)**




See next page for load pull information

discontinued product



### Load Pull Performance



Main side pulsed CW signal: 160  $\mu$ sec, 10% duty cycle,  $V_{DD} = 26$  V,  $I_{DQ} = 120$  mA

Class AB		P <sub>1dB</sub>									
		Max Output Power					Max PAE				
Freq [MHz]	Z <sub>s</sub> [ $\Omega$ ]	Z <sub>l</sub> [ $\Omega$ ]	Gain [dB]	P <sub>OUT</sub> [dBm]	P <sub>OUT</sub> [W]	PAE [%]	Z <sub>l</sub> [ $\Omega$ ]	Gain [dB]	P <sub>OUT</sub> [dBm]	P <sub>OUT</sub> [W]	PAE [%]
2110	19.70 – j30.49	11.34 – j3.06	20.9	43.74	23.7	59.4	11.02 – j3.49	22.3	42.70	18.6	66.0
2140	17.03 – j36.14	9.73 – j2.15	20.9	43.48	22.3	58.6	9.78 – j3.58	22.9	42.26	16.8	64.6
2170	34.36 – j32.08	10.27 – j2.68	20.8	43.71	23.5	58.4	9.47 – j3.32	22.5	42.53	17.9	64.6


Peak side pulsed CW signal: 160  $\mu$ sec, 10% duty cycle,  $V_{DD} = 26$  V,  $V_{GS(peak)} = 1.5$  V

Class C		P <sub>1dB</sub>									
		Max Output Power					Max PAE				
Freq [MHz]	Z <sub>s</sub> [ $\Omega$ ]	Z <sub>l</sub> [ $\Omega$ ]	Gain [dB]	P <sub>OUT</sub> [dBm]	P <sub>OUT</sub> [W]	PAE [%]	Z <sub>l</sub> [ $\Omega$ ]	Gain [dB]	P <sub>OUT</sub> [dBm]	P <sub>OUT</sub> [W]	PAE [%]
2110	9.80 – j12.90	3.28 – j4.71	15.5	47.56	57.0	60.7	4.00 – j1.52	16.5	45.6	36.3	71.8
2140	10.71 – j17.59	3.51 – j5.03	16.0	47.50	56.2	60.7	3.88 – j1.93	17.0	45.9	38.7	71.3
2170	15.51 – j13.51	3.58 – j5.14	15.6	47.53	56.6	60.0	3.69 – j1.47	16.6	45.4	34.9	70.9

### Reference Circuit, tuned for 2110 – 2170 MHz

DUT	PXAC210552FC
Test Fixture Part No.	LTA/PXAC210552FC V1
PCB	Rogers 4350, 0.508 mm [.020"] thick, 2 oz. copper, $\epsilon_r = 3.66$
Find Gerber files for this reference fixture on the Wolfspeed Web site at <a href="http://www.wolfspeed.com/RF">www.wolfspeed.com/RF</a>	

Reference Circuit (cont.)



Reference circuit assembly diagram (not to scale)

Component Information

Component	Description	Manufacturer	P/N
<b>Input</b>			
C101, C103, C105, C106	Capacitor, 18 pF	ATC	ATC600F180GW250T
C102	Capacitor, 0.5 pF	ATC	ATC600F0R5CW250T
C104	Capacitor, 0.8 pF	ATC	ATC600F0R8CW250T
C107, C108	Capacitor, 10 $\mu$ F	Taiyo Yuden	UMK325C7106MM-T
R101	Termination, 50 ohms	Anaren	C8A50Z4A
R102, R103	Resistor, 10 ohms	Panasonic	ERJ-3GEYJ100V
U1	Hybrid coupler	Anaren	X3C21P1-03S

table continued next page




**Reference Circuit** (cont.)

**Component Information** (cont.)

Component	Description	Manufacturer	P/N
<b>Output</b>			
C201	Capacitor, 5.1 pF	ATC	ATC600F5R1BW250T
C202, C204, C205, C207, C209	Capacitor, 18 pF	ATC	ATC600F180GW250T
C203	Capacitor, 0.8 pF	ATC	ATC600F0R8CW250T
C206	Capacitor, 0.1 μF	Panasonic	ECJ-3VB1H104K
C208	Capacitor, 220 μF	Cornell Dubilier Electronics (CDE)	SK221M050ST
C210, C211, C212, C213, C214, C215	Capacitor, 10 μF	Taiyo Yuden	UMK325C7106MM-T


**Pinout Diagram** (top view)



discontinued product



Package Outline Specifications



**For more information, please contact:**

4600 Silicon Drive  
Durham, NC 27703 USA  
Tel: +1.919.313.5300  
[www.wolfspeed.com/RF](http://www.wolfspeed.com/RF)

Sales Contact  
[RFSales@wolfspeed.com](mailto:RFSales@wolfspeed.com)

RF Product Marketing Contact  
[RFMarketing@wolfspeed.com](mailto:RFMarketing@wolfspeed.com)

discontinued product

## Notes & Disclaimer

---

Specifications are subject to change without notice. “Typical” parameters are the average values expected by Wolfspeed in large quantities and are provided for information purposes only. Wolfspeed products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.