

Product data sheet

Specifications



Photoelectric sensors XU, 24 VDC PNP 1 NO / 1 NC

XUN0APSNM12

Main

| | |
|-------------------------------|---|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | General purpose multimode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUB |
| Sensor design | American form |
| Detection system | Multimode |
| Material | Plastic |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 3-wire |
| Discrete output type | PNP |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | 1 male connector M12, 4 pins |
| Product specific application | - |
| Emission | Infrared diffuse Infrared diffuse with background suppression Infrared thru beam Red polarised reflex |
| [Sn] nominal sensing distance | 3 m polarised reflex need reflector XUZC50 0.12 m diffuse with background suppression 0.3 m diffuse 20 m thru beam need a transmitter XUN0SKSNM12T |

Complementary

| | |
|--------------------------|---|
| Enclosure material | PBT |
| Lens material | PMMA |
| Maximum sensing distance | 0.12 m diffuse with background suppression 0.4 m diffuse 30 m thru beam 4.5 m polarised reflex |
| Output type | Solid state |
| Add on output | With alarm output, <= 50 mA with overload and short-circuit protection |
| Status LED | 1 LED (green) for supply 1 LED (red) for instability 1 LED (yellow) for output state |

| | |
|----------------------------------|---|
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply voltage limits | 10...36 V DC |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) |
| Switching frequency | <= 250 Hz |
| Maximum voltage drop | <1.5 V (closed state) |
| Current consumption | <= 35 mA no-load |
| Maximum delay first up | 200 ms |
| Maximum delay response | 2 ms |
| Maximum delay recovery | 2 ms |
| Setting-up | Self-teaching |
| Diameter | 18 mm |
| Depth | 66 mm |
| Height | 45 mm |
| Width | 18 mm |
| Net weight | 0.09 kg |

Environment

| | |
|--|---|
| Product certifications | CE UL CSA |
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27 |
| IP degree of protection | IP65 double insulation conforming to IEC 60529 |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.412 cm |
| Package 1 Width | 8.412 cm |
| Package 1 Length | 8.412 cm |
| Package 1 Weight | 58.967 g |

Offer Sustainability

| | |
|----------------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Recommended replacement(s)