

# DATA SHEET

## MELF CARBON FILM RESISTORS

General Purpose

MCF Series

$\pm 2\%$ ,  $\pm 5\%$

1/6W to 1W

RoHS compliant & Halogen Free





**APPLICATIONS**

- All general purpose applications
- Power applications
- Energy meter

**FEATURES**

- MELF, SMD package
- Excellent pulse withstanding capability
- Wide resistance range
- RoHS compliant & halogen-free

**ORDERING INFORMATION**

Part number of the MELF carbon film resistor is identified by the series, power rating, tolerance, packing, temperature coefficient and resistance value.

**PART NUMBER**

<u>MCF</u> (1)	<u>25S</u> (2)	<u>J</u> (3)	<u>R</u> (4)	<u>-</u> (5)	<u>100R</u> (6)
-------------------	-------------------	-----------------	-----------------	-----------------	--------------------

---

**(1) SERIES**

MCF Series

---

**(2) POWER RATING**

-12 = 1/6W	50S = 1/2W
25S = 1/4W	207 = 0.6W
204 = 0.4W	-50 = 1/2W
-25 = 1/4W	1WS = 1W

---

**(3) TOLERANCE**

G = ±2%	- = Based on spec.
J = ±5%	

---

**(4) PACKAGING**

R = Reel Pack

---

**(5) TEMPERATURE COEFFICIENT OF RESISTANCE**

- = Based on spec.

---


**(6) RESISTANCE VALUE**

E24 Series value  
 Example:  
 1R = 1Ω, 10K = 10,000Ω, 1M = 1,000,000Ω

---

**DIMENSIONS**


Unit: mm



Normal	Miniature	L	D	C Min.
MCF-12	MCF25S / MCF204	3.50 ± 0.2	1.40 ± 0.15	0.5
MCF-25	MCF50S / MCF207	5.90 ± 0.2	2.20 ± 0.1	0.5
MCF-50	MCF1WS	8.50 ± 0.2	3.20 ± 0.2	0.5


**SUGGESTED PAD LAYOUT**

Unit: mm



Normal	Miniature	Soldering Mode	L Min.	P	W Min.
MCF-12	MCF25S MCF204	Reflow	1.3	1.6 ± 0.1	1.6
		Wave	1.5	1.5 ± 0.1	1.8
MCF-25	MCF50S MCF207	Reflow	2.0	3.0 ± 0.1	3.0
		Wave	2.5	3.0 ± 0.1	3.0
MCF-50	MCF1WS	Reflow	2.3	5.5 ± 0.2	4.0
		Wave	2.8	5.5 ± 0.2	4.0

**DERATING CURVE**



**TABLE I TEMPERATURE COEFFICIENT**

TYPE	MAX. VALUE OF TEMP. COEFFICIENT PPM/ °C			
	under 1KΩ	1K1Ω – 47KΩ	51KΩ – 470KΩ	510KΩ – 1MΩ
MCF-12, MCF25S, MCF204	0 ~ -350	0 ~ -600	0 ~ -1000	0 ~ -1500
MCF-25, MCF50S, MCF207, MCF-50, MCF1WS	0 ~ -350	0 ~ -600	0 ~ -1000	

## ELECTRICAL CHARACTERISTICS

CHARACTERISTICS	MCF-12	MCF25S	MCF204	MCF-25	MCF50S	MCF207	MCF-50	MCF1WS
Power Rating at 70 °C	1/6W	1/4W	0.4W	1/4W	1/2W	0.6W	1/2W	1W
Maximum Working Voltage	200V	250V	250V	300V	300V	300V	350V	350V
Maximum Overload Voltage	400V	500V	500V	600V	600V	600V	700V	700V
Voltage Proof on Insulation	200V	200V	200V	500V	500V	500V	700V	700V
Resistance Range	10Ω ~ 1MΩ & 0Ω for E24 series value							
Operating Temp. Range	- 55°C to +155°C							
Temperature Coefficient	see Table I							

Note: For resistance value out of above range is by request.

## TEST AND REQUIREMENTS

TEST	TEST METHOD	PROCEDURE	APPRAISE
Short Time Overload	IEC 60115-1 4.13	2.5 times RCWV for 5 sec.(Not more than maximum overload voltage)	±1.0%+0.05Ω
Voltage Proof on Insulation	IEC 60115-1 4.7	In V-Block for 60 sec. test voltage as above table	No Breakdown
Temperature Coefficient	IEC 60115-1 4.8	Between -55°C to +155°C	By Type
Insulation Resistance	IEC 60115-1 4.6	In V-Block for 60 sec.	>10,000MΩ
Solderability	IEC 60115-1 4.17	245±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Periodic-pulse Overload	IEC 60115-1 4.39	4 times RCWV 10,000 cycles (1 Sec. on, 25 Sec.off)	±1.0%+0.05Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C,90-95% RH for 56 days, loaded with 0.1 times RCWV	±5.0%+0.05Ω
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV(or Umax., whichever less) for 1,000 Hr.(1.5 Hr.on,0.5 Hr. off)	±3.0%+0.05Ω
Temperature Cycling	IEC 60115-1 4.19	→ -55°C → Room Temp. → +155°C Room Temp.(5 cycles)	±0.75%+0.05Ω
Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±1.0%+0.05Ω

Note:

### RCWV (Rated Continuous Working Voltage ):

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V=\sqrt{(P \times R)}$$

or max. working voltage whichever is less

Where

V=Continuous rated DC or  
AC (rms) working voltage (V)

P=Rated power (W)

R=Resistance value ( $\Omega$ )


### PACKING

TYPE				Unit: piece
Normal	Miniature	Packaging	Quantity Per Reel	
MCF-12	MCF25S MCF204	7"	3,000	
MCF-25	MCF50S MCF207	7"	2,000	
MCF-50	MCF1WS	13"	2,500	

**MARKING**

3-BAND-CODE

±2%, ±5%



COLOR	1st BAND	2nd BAND	MULTIPLIER
BLACK	0	0	1Ω
BROWN	1	1	10Ω
RED	2	2	100Ω
ORANGE	3	3	1KΩ
YELLOW	4	4	10KΩ
GREEN	5	5	100K
BLUE	6	6	1MΩ
VIOLET	7	7	10MΩ
GREY	8	8	0.001Ω
WHITE	9	9	0.0001Ω
GOLD			0.1Ω
SILVER			0.01Ω

**REVISION HISTORY**

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Version 0	Aug. 2, 2021	-	- First issue of this specification

*“ Yageo reserves all the rights for revising the content of this datasheet without further notification, as long as the products itse lf are unchanged. Any product change will be announced by PCN.”*

### LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial, automotive, and/or COTS grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.