SIEMENS

Data sheet



Illuminated pushbutton, 22 mm, round, plastic, amber, pushbutton, flat momentary contact type, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

SIRIUS ACT	
Illuminated pushbuttons	
Actuating/signaling element	
3SU1	
Plastic, black, 22 mm	
Enclosure	
1	
Actuator	
Flat button	
momentary contact type	
Yes	
Yes	
amber	
plastic	
round	
29.5 mm	
Customized labeling, graphical symbols acc. to ISO7000 and IEC60417	
Yes	
Standard	
plastic	
black	
IP66, IP67, IP69(IP69K)	
IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13	
1, 2, 3, 3R, 4, 4X, 12, 13	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h	
1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 3 000 000	

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AB00-0AA0-Z Y13

Cax online generator

 $\underline{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1001-0AB00-0AA0-Z\ Y13-0AB00-0AA0-Z\ Y13-0AB00-0AA0-Z\$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AB00-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AB00-0AA0-Z Y13&lang=en

last modified: 12/21/2020 🖸