



Illuminated twin pushbutton, 22 mm, round, plastic, white: Symbol circular saw blade, white: Symbol dump body tipping, pushbuttons, flat

|  |  |
|--|--|
| product brand name                                 | SIRIUS ACT                                       |
| product designation                                | Twin pushbuttons                                 |
| design of the product                              | Actuating/signaling element                      |
| product type designation                           | 3SU1   |
| product line                                       | Plastic, black, 22 mm                            |
| <b>Enclosure</b>                                   |  |
| number of command points                           | 1  |
| <b>Actuator</b>                                    |  |
| design of the actuating element                    | Flat buttons, illuminated                        |
| principle of operation of the actuating element    | momentary contact type                           |
| product extension optional                         |  |
| • light source                                     | Yes  |
| • contact module                                   | Yes  |
| color of the actuating element                     | white / white                                    |
| material of the actuating element                  | plastic  |
| shape of the actuating element                     | oval   |
| marking of the actuating element                   | Top: "buzz saw blade";bottom:"dump body tilting" |
| <b>Front ring</b>                                  |  |
| product component front ring                       | Yes  |
| design of the front ring                           | Standard   |
| material of the front ring                         | plastic  |
| color of the front ring                            | black  |
| <b>General technical data</b>                      |  |
| protection class IP                                | IP66, IP67, IP69(IP69K)                          |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                       |
| shock resistance                                   |  |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms                 |
| • for railway applications according to EN 61373   | Category 1, Class B                              |
| vibration resistance                               |  |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                                |
| • for railway applications according to EN 61373   | Category 1, Class B                              |
| operating frequency maximum                        | 3 600 1/h  |
| mechanical service life (switching cycles) typical | 2 000 000  |
| reference code according to IEC 81346-2            | S  |
| Substance Prohibitance (Date)                      | 10/01/2014                                       |
| <b>Ambient conditions</b>                          |  |
| ambient temperature                                |  |
| • during operation                                 | -25 ... +70 °C                                   |
| • during storage                                   | -40 ... +80 °C                                   |

|  |  |
|--|--|
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
|--|--|

| Installation/ mounting/ dimensions          |         |
|---|---------|
| height                                      | 57.9 mm |
| width                                       | 29.9 mm |
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 14.4 mm |
| installation width                          | 29.9 mm |
| installation depth                          | 25.7 mm |

| Certificates/ approvals  |                           |
|--------------------------|---------------------------|
| General Product Approval | Declaration of Conformity |



[Confirmation](#)



EG-Konf.

| Test Certificates | Marine / Shipping |
|-------------------|-------------------|
|-------------------|-------------------|

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



RINA



RMRS

| other |
|-------|
|-------|

[Confirmation](#)

[Environmental Confirmations](#)

| Further information |
|---------------------|
|---------------------|

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-3AB66-0AP0>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-3AB66-0AP0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-3AB66-0AP0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1001-3AB66-0AP0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-3AB66-0AP0&lang=en)



last modified:

1/26/2022 