

SIMATIC CP1625, PCIe card for PROFINET IRT for Softwarecontroller CPU1500S



Figure similar

General information	
Product function	
<ul style="list-style-type: none"> <li>Proxy functionality</li> </ul>	No
Installation type/mounting	
Design	Plug-in card
Supply voltage	
Type of supply voltage	DC via PCI Express
Interfaces	
Interfaces/bus type	PROFINET IO
Number of PROFINET interfaces	1; 2 ports (switch)
Integrated Functions	
Monitoring functions	
<ul style="list-style-type: none"> <li>Status LEDs</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Fan</li> </ul>	No
EMC	
Interference immunity against discharge of static electricity	
<ul style="list-style-type: none"> <li>Interference immunity against discharge of static electricity</li> </ul>	all EMC immunity requirements according to SPH Environment Specification V4.2 HMI / IPC Class 1
Interference immunity against high-frequency electromagnetic fields	
<ul style="list-style-type: none"> <li>Interference immunity against high frequency radiation</li> </ul>	all EMC immunity requirements according to SPH Environment Specification V4.2 HMI / IPC Class 1
Interference immunity to cable-borne interference	
<ul style="list-style-type: none"> <li>Interference immunity on supply cables</li> </ul>	all EMC immunity requirements according to SPH Environment Specification V4.2 HMI / IPC Class 1
Standards, approvals, certificates	
CE mark	Yes; CE marking / EC Declaration of Conformity
CSA approval	Yes
UL approval	Yes; UL 60950
cULus	Yes
FM approval	No
KC approval	Yes
EMC	EN 61000-6-3, FCC Class A, EN 61000-6-4, CISPR 22, EN 55022 Class B, EN 61000-3-2 Class D, EN 61000-3-3
Use in hazardous areas	
<ul style="list-style-type: none"> <li>ATEX Zone 2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>IECEX Zone 2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>FM Class I Division 2</li> </ul>	No

Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Korean Register of Shipping (KRS)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (Class NK)	Yes
Ambient conditions	
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 000 m
Relative humidity	
• Relative humidity	5 % to 90 % at 40 °C (no condensation)
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	1 g (10 m/s <sup>2</sup> )
Shock testing	
• Shock load during operation	5 g (50 m/s <sup>2</sup> )
Dimensions	
Width	21.6 mm
Height	126 mm
Depth	180 mm
<b>last modified:</b>	3/7/2020 