SIEMENS

Data sheet

3SU1051-1BA50-0AA0-Z Y11



Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, blue, 40 mm, latching, pull-to-unlatch mechanism, with laser labeling, upper case

product brand name	SIRIUS ACT
product designation	Mushroom pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Metal, shiny, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	illuminated
principle of operation of the actuating element	latching
product extension optional light source	Yes
color of the actuating element	blue
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	40 mm
marking of the actuating element	Customized labeling, text in capital letters
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
product component front ring design of the front ring	Yes Standard
design of the front ring	Standard
design of the front ring material of the front ring	Standard Metal, high gloss
design of the front ring material of the front ring color of the front ring	Standard Metal, high gloss
design of the front ring material of the front ring color of the front ring General technical data	Standard Metal, high gloss
design of the front ring material of the front ring color of the front ring General technical data product function	Standard Metal, high gloss silver
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function	Standard Metal, high gloss silver
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function	Standard Metal, high gloss silver
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K)
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (switching cycles) typical	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000
design of the front ring material of the front ring color of the front ring General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (switching cycles) typical reference code according to IEC 81346-2	Standard Metal, high gloss silver No No IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000 S

during operation	-25 +70 °C
during storage	-40 +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)

Installation/ mounting/ dimensions	
height	40 mm
width	40 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	27.5 mm
installation width	40 mm
installation depth	24.4 mm
Certificates/ approvals	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-1BA50-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1051-1BA50-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-1BA50-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1051-1BA50-0AA0-Z Y11&lang=en

last modified:

1/27/2022 🖸