3SU1001-0AD70-0AA0-Z Y15

Data sheet



Indicator light in illuminated pushbutton design, 22 mm, round, plastic, clear, with laser labeling, upper case and lower case, always upper case at the beginning of the word

product designation
design of the product product type designation product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element principle of operation of the actuating element lilluminated pushbutton design principle of operation of the actuating element product extension optional light source contact module color of the actuating element material of the actuating element plastic shape of the actuating element outer diameter of the actuating element customized labeling, text in lower case / capital letters, all words start with capital letters
product type designation product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element principle of operation of the actuating element elight source contact module color of the actuating element material of the actuating element shape of the actuating element plastic shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
product line Plastic, black, 22 mm Enclosure number of command points 1 Actuator design of the actuating element Illuminated pushbutton design principle of operation of the actuating element Fixed key product extension optional • light source Yes • contact module Yes color of the actuating element clear material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
Illuminated pushbutton design principle of operation of the actuating element product extension optional light source color of the actuating element praterial of the actuating element plastic shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
Actuator design of the actuating element Illuminated pushbutton design
design of the actuating element principle of operation of the actuating element product extension optional light source contact module color of the actuating element color of the actuating element plastic shape of the actuating element outer diameter of the actuating element customized labeling, text in lower case / capital letters, all words start with capital letters
principle of operation of the actuating element product extension optional light source
product extension optional Ight source Contact module Color of the actuating element Clear Material of the actuating element Shape of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
 light source contact module color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
● contact module Color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
shape of the actuating elementroundouter diameter of the actuating element29.5 mmmarking of the actuating elementCustomized labeling, text in lower case / capital letters, all words start with capital letters
outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
marking of the actuating element Customized labeling, text in lower case / capital letters, all words start with capital letters
with capital letters
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
General technical data
protection class IP IP66, IP67, IP69(IP69K)
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance
• acc. to IEC 60068-2-27 Sinusoidal half-wave 50g / 11 ms
• for railway applications acc. to DIN EN 61373 Category 1, Class B
vibration resistance
• acc. to IEC 60068-2-6 10 500 Hz: 5g
• for railway applications acc. to DIN EN 61373 Category 1, Class B
reference code acc. to IEC 81346-2
Ambient conditions
• ambient temperature during operation -25 +70 °C
• ambient temperature during storage -40 +80 °C

environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AD70-0AA0-Z Y15

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0AD70-0AA0-Z Y15

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AD70-0AA0-Z Y15

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AD70-0AA0-Z Y15&lang=en

last modified:	1/18/2021	3