



Figure similar

SIMATIC S7-1200, Analog input, SM 1231, 8 AI, +/-10 V, +/-5 V, +/-2.5 V, or 0-20 mA/4-20 mA, 12 bit+sign or (13 bit ADC)

General information	
Product type designation	SM 1231, AI 8x13 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	90 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 $\mu$ s
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> <li>• Resistance</li> </ul>	Yes; $\pm 10V$ , $\pm 5V$ , $\pm 2.5V$ Yes; 4 to 20 mA, 0 to 20 mA No No Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -10 V to +10 V — Input resistance (-10 V to +10 V)</li> <li>• -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V)</li> <li>• -5 V to +5 V — Input resistance (-5 V to +5 V)</li> </ul>	Yes $\geq 9$ MOhm Yes $\geq 9$ MOhm Yes $\geq 9$ MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA — Input resistance (0 to 20 mA)</li> <li>• 4 mA to 20 mA — Input resistance (4 mA to 20 mA)</li> </ul>	Yes 280 $\Omega$ Yes 280 $\Omega$
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Analog value generation for the inputs	

<b>Integration and conversion time/resolution per channel</b>	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> <li>Integration time, parameterizable</li> <li>Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	12 bit; + sign Yes 40 dB, DC to 60 V for interference frequency 50 / 60 Hz
<b>Smoothing of measured values</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> <li>Step: None</li> <li>Step: low</li> <li>Step: Medium</li> <li>Step: High</li> </ul>	Yes Yes Yes Yes Yes
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	25 °C $\pm 0.1\%$ , to 55 °C $\pm 0.2\%$ total measurement range
<b>Basic error limit (operational limit at 25 °C)</b>	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Current, relative to input range, (+/-)</li> </ul>	0.1 % 0.1 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1 =</math> interference frequency</b>	
<ul style="list-style-type: none"> <li>Common mode voltage, max.</li> </ul>	12 V
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> </ul>	Yes Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>for status of the inputs</li> <li>for maintenance</li> </ul>	Yes Yes
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
<b>Free fall</b>	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
<ul style="list-style-type: none"> <li>Operation, min.</li> <li>Operation, max.</li> <li>Storage/transport, min.</li> <li>Storage/transport, max.</li> </ul>	795 hPa 1 080 hPa 660 hPa 1 080 hPa
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>Operation at 25</li> </ul>	95 %

°C without condensation, max.	
<b>Pollutant concentrations</b>	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>connection method / header</b>	
required front connector	Yes
<b>Mechanics/material</b>	
Enclosure material (front)	
• Plastic	Yes
<b>Dimensions</b>	
Width	45 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	180 g
<b>last modified:</b>	2/26/2021 