

9012GAWM4H3

9012G, pressure switch 9012 g, adjustable scale, 2 thresholds, 1.5 to 75 PSIG



Main

| | |
|-----------------------------------|---|
| Range of Product | 9012G |
| Pressure sensor type | Electromechanical pressure switch |
| Pressure sensor name | 9012G |
| Pressure Rating | 75 psi (517.11 kPa) |
| Maximum pressure | 240 psi |
| Contacts type and composition | NC-NO, SPDT-DB, Form Z, snap action, silver nickel contacts |
| Controlled fluid | Hydraulic oil -40...250 °F (-40...121 °C)) Non-corrosive liquids Air Non-corrosive gas |
| Fluid connection type | 0.25 inch BS2779 parallel pipe thread UL 508 |
| Pressure switch type of operation | Regulation between 2 thresholds |
| Scale type | Adjustable differential |
| Local display | Without |

Complementary

| | |
|---|---|
| Range on decreasing pressure | 1.5...75 psi (10.34...517.11 kPa) |
| Approx adjustable differential at mid range | 3.5...15 psi (24.13...103.42 kPa) +/- 2.5 % full scale |
| Cable entry | 20 mm BS4568 conduit entrance |
| Terminal block type | 4 screw terminals |
| Electrical connection | Screw-clamp terminals, AWG 22...AWG 12 |
| Electrical circuit type | Control circuit |
| Local signalling | Without |
| Line Rated Current | 1.1 A 125 V DC |
| Setting | Internal |
| Enclosure Material | Die cast aluminium alloy 380 |
| Pressure actuator | Diaphragm nitrile (Buna-N) |
| Height | 5.55 in (140.97 mm) |
| Depth | 2.63 in (66.80 mm) |
| Width | 3.5 in (88.90 mm) |
| Operating position | Any position |
| Materials in contact with fluid | Nitrile (Buna-N) Zinc plated steel |
| Short-circuit protection | 10 A cartridge overload and short-circuit protection gL |
| Maximum operating rate | 120 cyc/mn |
| Mechanical durability | 5000000 cycles |
| Repeat accuracy | 4 % |
| Net Weight | 3 lb(US) (1.36 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Vibration resistance | 2 gn 40...150 Hz)IEC 68-2-6 |
| Shock resistance | 50 gn IEC 58-2-27 |
| Standards | CSA C22.2 No 14 CE UL 508 |
| Product Certifications | UL listed file E12158 CCN NKPZ and CCN NTHT CE CSA LR25490 class 3211 03 |
| NEMA degree of protection | NEMA 4/4X/13 UL 50 |
| Ambient air temperature for operation | -10...185 °F (-23...85 °C) |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 21522 - 9012 G INDUSTRIAL PRESSURE SWITCHES |
| Discount Schedule | CP7G |
| GTIN | 785901182658 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.00 lb(US) (1.361 kg) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 24.13 in (61.29 cm) |
| Package 1 width | 9.50 in (24.13 cm) |
| Package 1 Length | 61.29 in (155.677 cm) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|