



### Main

|                             |   |
|-----------------------------|---|
| Range                       | Spacial   |
| Product name                | Spacial VDM   |
| Application                 | Electronic application  |
| Product or Component Type   | Compact enclosure   |
| Body type                   | 1-body  |
| Rack type                   | Swing   |
| Enclosure nominal height    | 19.69 in (500 mm)   |
| Enclosure nominal width     | 23.62 in (600 mm)   |
| Enclosure nominal depth     | 15.75 in (400 mm)   |
| Installation accessory type | Wall-mounting   |
| Product destination         | Electronics and networks  |
| Device composition          | 1 cable gland plate bottom<br>2 lock 19" swing rack<br>1 body<br>1 door with lock<br>1 19" swing rack |

### Complementary

|                             |   |
|-----------------------------|---|
| Door type                   | Glass   |
| Number of doors             | Front face 1                                  |
| Door opening side           | Reversible 120 °)                             |
| Lock type                   | 3 mm double-bar lock                          |
| Type of gland plate         | Standard                                      |
| Number of units 19"         | 9   |
| Accessibility for operation | Front   |
| Removable parts             | Door by hinges<br>Rack by fixing element      |
| Material                    | Enclosure and 19" rack steel                  |
| Surface finish              | Enclosure and 19" rack epoxy-polyester powder |
| Color                       | Enclosure and 19" rack Gray RAL 7035)         |
| Standards                   | IEC 62208                                     |
| Net Weight                  | 50.53 lb(US) (22.92 kg)                       |
| Width                       | 23.62 in (600 mm)                             |
| Height                      | 19.69 in (500 mm)                             |
| Depth                       | 15.75 in (400 mm)                             |

### Environment

|                         |                |
|-------------------------|----------------|
| IP degree of protection | IP66 IEC 60529 |
| IK degree of protection | IK08 IEC 62262 |

## Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 80034-ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule     | ES1                                      |
| GTIN                  | 3606480174520                            |
| Nbr. of units in pkg. | 1  |
| Package weight(Lbs)   | 50.53 lb(US) (22.92 kg)                  |
| Returnability         | No                                       |
| Country of origin     | FR                                       |

## Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 24.41 in (62.0 cm) |
| Package 1 width        | 20.87 in (53.0 cm) |
| Package 1 Length       | 16.54 in (42.0 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|