



SIMATIC ET 200AL, PROFINET interface module IM 157-1 PN, Degree of protection IP67

| General information | |
|--|--------------------------|
| Product type designation | IM 157-1 PN |
| HW functional status | FS02 |
| Firmware version | V1.0.x |
| Vendor identification (VendorID) | 002AH |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M4 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | STEP 7 V13 SP1 or higher |
| <ul style="list-style-type: none"> STEP 7 configurable/integrated from version | From V5.5 SP4 Hotfix 3 |
| <ul style="list-style-type: none"> PROFINET from GSD version/GSD revision | GSDML V2.3.1 |
| Configuration control | |
| via dataset | Yes |
| Supply voltage | |
| power supply according to NEC Class 2 required | No |
| Load voltage 1L+ | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V |
| <ul style="list-style-type: none"> permissible range, lower limit (DC) | 20.4 V |
| <ul style="list-style-type: none"> permissible range, upper limit (DC) | 28.8 V |
| <ul style="list-style-type: none"> Reverse polarity protection | Yes; against destruction |
| Input current | |
| Current consumption (rated value) | 100 mA |
| from load voltage 1L+ (unswitched voltage) | 4 A; Maximum value |
| from load voltage 2L+, max. | 4 A; Maximum value |
| Power loss | |
| Power loss, typ. | 2.9 W |
| Address area | |
| Address space per station | |
| <ul style="list-style-type: none"> Address space per station, max. | 1 430 byte |
| Interfaces | |
| Number of PROFINET interfaces | 1 |
| 1. Interface | |
| Interface type | PROFINET |
| Interface types | |
| <ul style="list-style-type: none"> M12 port | Yes; 2x M12 D-coded |
| <ul style="list-style-type: none"> integrated switch | Yes |
| Protocols | |
| <ul style="list-style-type: none"> PROFINET IO Device | Yes |

| | |
|---|--|
| • Open IE communication | Yes |
| Interface types | |
| M12 port | |
| • Transmission procedure | PROFINET with 100 Mbit/s full duplex (100BASE-TX) |
| • 10 Mbps | Yes; for Ethernet services |
| • 100 Mbps | Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX) |
| • Autonegotiation | Yes |
| • Autocrossing | Yes |
| Protocols | |
| PROFINET IO Device | |
| Services | |
| — IRT | Yes; 250 µs, 500 µs, 1 ms, 2 ms, 4 ms, 8 ms, 16 ms, 32 ms, 64 ms, 128 ms |
| — PROFIenergy | Yes |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 4 |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes |
| — MRPD | Yes |
| Open IE communication | |
| • TCP/IP | Yes |
| • SNMP | Yes |
| • LLDP | Yes |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| Diagnostics indication LED | |
| • RUN LED | Yes; green LED |
| • ERROR LED | Yes; red LED |
| • MAINT LED | Yes; Yellow LED |
| • Connection display LINK TX/RX | Yes; 2x green LED |
| Potential separation | |
| between the load voltages | Yes |
| between PROFINET and all other circuits | Yes |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Degree and class of protection | |
| IP degree of protection | IP65/67 |
| Standards, approvals, certificates | |
| Suitable for safety-related tripping of standard modules | Yes; From FS01 |
| Highest safety class achievable for safety-related tripping of standard modules | |
| • Performance level according to ISO 13849-1 | PL d |
| • Category according to ISO 13849-1 | Cat. 3 |
| • SIL acc. to IEC 62061 | SIL 2 |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -25 °C |
| • max. | 55 °C |
| connection method / header | |
| Design of electrical connection for supply voltage | M8, 4-pole |
| ET-Connection | |
| • ET-Connection | M8, 4-pin, shielded |
| Dimensions | |
| Width | 45 mm |
| Height | 159 mm |
| Depth | 40 mm |

Weights

Weight, approx.

263 g

last modified:

3/7/2022 