



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. 30A 3P 600V FUSED RECEIPT SW TP12 W/WINDO

|  |   |
|--|---|
| mechanical service life (switching cycles) typical | 10000   |
| fastening method                                   | SURFACE   |
| number of poles                                    | 3   |
| suitability for operation                          | PROTECTION OF HEAVY DUTY PORTABLE EQUIPMENT       |
| <b>Electricity</b>                                 |   |
| ampacity   | 30 A  |
| supply voltage frequency rated value 50/60 Hz      | Yes   |
| <b>Environmental conditions</b>                    |   |
| ambient temperature during operation maximum       | 85 °C   |
| ambient temperature during operation minimum       | -29 °C  |
| <b>Model</b>                                       |   |
| product brand name                                 | SIEMENS   |
| product sub brand name                             | VBII  |
| product type designation                           | HEAVY DUTY SWITCH                                 |
| special product feature                            | ACCEPTS CROUSE-HINDS Arktite PLUGS VIEWING WINDOW |
| type of electrical connection                      | INTERLOCKED PLUG                                  |
| <b>Mechanical Design</b>                           |   |
| design of the housing                              | TYPE 12   |
| design of the actuating element                    | SINGLE THROW                                      |
| material   | STEEL   |
| <b>General product approval</b>                    |   |
| certificate of suitability                         | UL98  |

last modified:

9/15/2021 

