

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/25/20	

RECOMMENDED PCB LAYOUT

20.0
12.29
2- ϕ 1.10

ϕ 22.3

24.0
7.60

0.70

0.50

7.50
8.80
3-1.5
20.0 \pm 0.3
3.6

SPECIFICATIONS:

Material:

Housing: PBT, rated UL94V-0, Color: Black

Contact: Brass, Nickel plated

Electrical:

Contact resistance: 30 Milliohms max

Insulation resistance: 1,000 Megaohms ohms min

Dielectric Voltage: 1,000 VAC @ sea level

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
MM ANGLE

X	\pm 0.30	X	\pm 1°
X.X	\pm 0.25	X.X	\pm 0.5°
X.XX	\pm 0.20		
X.XXX	\pm 0.10		

ADAM
TECH
INTERCONNECTS

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

APPROVALS		DATE
DRAWN	LH	3/25/20
CHECKED	MY	3/25/20
APPROVED		

TITLE			
BATTERY HOLDER, PIN LEADS FOR CR2032 CELLS			
SIZE	PART NO.	REV.	
X	BH-68A-1	-	
REF:	S00136C	SCALE: NTS	SHEET 1 OF 1

6

5

4

3

2

1