

## External 240V Tower Battery Pack for select Tripp Lite UPS Systems (BP240V500)

MODEL NUMBER: **BP240V500**



### Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 240VDC configuration
- Hardwire installation
- Internal DC disconnect
- 10 year design lifespan
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Description

Tripp Lite's BP240V500 External Battery Pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes 15-ft. (4.57 m) cable to connect to UPS or additional battery pack.

COMPATIBLE UPS SYSTEMS: SU20K3/3, SU30K3/3 and other Tripp Lite UPS systems specifying the use of this battery pack

### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation

## Specifications

OVERVIEW	
UPC Code	037332185044
INPUT	
Input Phase	3-Phase
BATTERY	
Expandable Runtime	Yes
DC System Voltage (VDC)	240
UPS Connection	15ft / 4.6m DC cable connects to UPS or additional battery pack

<b>PHYSICAL</b>	
Material of Construction	Steel
External Battery Pack Form Factor	Tower
Shipping Dimensions (hwd / in.)	66.00 x 46.00 x 48.00
Shipping Dimensions (hwd / cm)	167.64 x 116.84 x 121.92
Shipping Weight (lbs.)	2590.00
Shipping Weight (kg)	1,174.80
Unit Dimensions (hwd / in.)	59.000 x 29.000 x 31.500
Unit Dimensions (hwd / cm)	149.9 x 73.7 x 80
Unit Weight (lbs.)	2480
Unit Weight (kg)	1,124.91
Unit Weight Details	Floor loading of 360 lbs per sq. ft. / 1762 kg per sq. meter
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	UKCA
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	1-year limited warranty