

External 36V 2U Rack/Tower Battery Pack for Select UPS Systems (BP36V15-2U)

MODEL NUMBER: BP36V15-2U



Highlights

- Extends the runtime of compatible 36V UPS Systems
- Supports 2U rack-mount installation; 4-post installation accessories included
- Options for 2-post rack-mount, tower and wall-mount installation available

Package Includes

- BP36V15-2U external battery pack with attached DC cabling
- 4 post compatible mounting hardware
- Owner's manual

Description

BP36V15-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with expandable 36V rack-mount and tower UPS systems. Includes heavy-gauge cabling with high-current DC connector for safe, simple installation. Included mounting accessories support 2U rack-mount installation in 4-post racks. Options for 2-point front-rail mounting, 2-post center-mounting, wall-mount and upright tower installation available.

Compatible with SMART1000RMXL2U, SMART1200XLHG, SMART1500RMXL2Ua, SMART1500XL, SMX1200XLHG, SMX1500XLRT2U and other UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible 36V DC UPS systems
- Includes heavy-gauge cabling with high-current DC connectors for simple installation
- Included mounting brackets support rack-mount installation in 4-post racks using only 2 rack spaces (2U)
- UPDHDEARKIT option supports two-point front-rail rack-mount installation without rear supports
- 2POSTRMKITWM option supports balanced two-point center-mounting in 2-post equipment racks
- 2POSTRMKITWM option also enables wallmount installation
- 2-9USTAND option enables upright tower placement
- NOTE: LIMIT OF 1 BP36V15-2U PER UPS, SEE BP36V42-3U or BP36V27-2US FOR MULTI-PACK COMPATIBILITY

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332119919 |
| INPUT | |

| | |
|---|---|
| Input Phase | Single-Phase |
| BATTERY | |
| DC System Voltage (VDC) | 36 |
| UPS Connection | Grey 2-point connector |
| Typical Battery Lifespan | 4-6 years typical |
| PHYSICAL | |
| Material of Construction | Steel |
| Rack Height | 2U |
| External Battery Pack Form Factor | Rack/Tower |
| Included Mounting Accessory Description | Included 4POSTRAILKIT mounting bracket enables installation in 4 post racks from 20.5 to 36 inches (521 to 914mm) |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount (2POSTRMKITWM); 4 post rackmount short-depth (4POSTRAILKITWM); Tower (2-9USTAND); Wallmount (2POSTRMKITWM) |
| Minimum Required Rack Depth (cm) | 43.18 |
| Minimum Required Rack Depth (inches) | 17 |
| Optional Mounting Accessory Notes | Optional 2-9USTAND ; enables upright tower UPS placement; 2POSTRMKITWM ; enables wall-mount and 2-post rackmount installation; 4POSTRAILKITWM ; enables installation in 4-post short-depth racks from 14.5 to 23.5 inches (368 to 597mm) |
| Shipping Dimensions (hwd / in.) | 8.90 x 20.20 x 23.40 |
| Shipping Dimensions (hwd / cm) | 22.61 x 51.31 x 59.44 |
| Shipping Weight (lbs.) | 57.81 |
| Shipping Weight (kg) | 26.22 |
| Unit Dimensions (hwd / in.) | 3.500 x 17.500 x 13.250 |
| Unit Dimensions (hwd / cm) | 8,89 x 44,45 x 33,66 |
| Unit Weight (lbs.) | 45 |
| Unit Weight (kg) | 20.41 |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS; CE (Europe) |

TRIPP-LITE

by **EAT•N**

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| WARRANTY & SUPPORT | |
|---|-------------------------|
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |

TRIPP-LITE

by **EAT•N**

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.