## TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

### External Battery Pack for Select 3-Phase UPS Systems (BP480V40C)

#### MODEL NUMBER: BP480V40C



#### Description

The BP480V40C External Battery Pack offers extended battery runtime when used in conjunction with compatible UPS systems. Includes internal disconnect for battery isolation. Compatible UPS Systems: SU40K, SU60K, SU80K, SU20KX, SU40KX, SU60KX, SU80KX and other UPS systems specifying the use of this battery pack.

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible UPS systems
- Multiple battery packs can be daisy-chained to the UPS for even longer extended run operation

### **Specifications**

OVERVIEW		
UPC Code	037332141514	
INPUT		
Input Phase	3-Phase	
BATTERY		
Expandable Runtime	Yes	
DC System Voltage (VDC)	+/- 240VDC	
UPS Connection	Hardwire (contractor supplies wiring - see Owner's Manual for gauge recommendations)	
Typical Battery Lifespan	3-5 years typical (North America)	

#### Highlights

- Extends runtime of compatible UPS Systems using special "+/-" 240VDC configuration
- Hardwire installation

#### **Package Includes**

- BP480V40C external battery pack
- Warranty information
- Owner's Manual

# TRIPP-LITE

PHYSICAL	
Material of Construction	Steel
External Battery Pack Form Factor	Tower
Installation Form Factors Supported with Included Accessories	Tower
Shipping Dimensions (hwd / in.)	76.00 x 28.50 x 45.00
Shipping Dimensions (hwd / cm)	193.04 x 72.39 x 114.30
Shipping Weight (lbs.)	1780.00
Shipping Weight (kg)	807.39
Unit Dimensions (hwd / in.)	66.900 x 20.500 x 33.700
Unit Dimensions (hwd / cm)	169.9 x 52.1 x 85.6
Unit Weight (lbs.)	1603
Unit Weight (kg)	727.11
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.