## **SIEMENS**

## **Data sheet**



Mushroom pushbutton, 22 mm, round, metal, shiny, yellow, 40 mm, momentary contact type, with laser labeling, upper case and lower case, always upper case at beginning of line

product brand name	SIRIUS ACT	
product designation	Mushroom pushbuttons	
design of the product	Actuating/signaling element	
product type designation	3SU1	
product line	Metal, shiny, 22 mm	
Enclosure		
number of command points	1	
Actuator		
principle of operation of the actuating element	momentary contact type	
product extension optional light source	No	
color of the actuating element	yellow	
material of the actuating element	plastic	
shape of the actuating element	round	
outer diameter of the actuating element	40 mm	
marking of the actuating element	Customized labeling, text in lower case / capital letters, all lines start with capital letter	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	Standard	
material of the front ring	Metal, high gloss	
color of the front ring	silver	
General technical data		
product function		
<ul> <li>EMERGENCY OFF function</li> </ul>	No	
<ul> <li>EMERGENCY STOP function</li> </ul>	No	
protection class IP	IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance		
<ul> <li>according to IEC 60068-2-27</li> </ul>	sinusoidal half-wave 15g / 11 ms	
vibration resistance		
<ul><li>according to IEC 60068-2-6</li></ul>	10 500 Hz: 5g	
operating frequency maximum	3 600 1/h	
mechanical service life (switching cycles) typical	10 000 000	
reference code according to IEC 81346-2	S	
Substance Prohibitance (Date)	10/01/2014	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-25 +70 °C	

during storage	-40 +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
Installation/ mounting/ dimensions	
height	40 mm
width	40 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	27.5 mm
installation width	40 mm
installation depth	24.4 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-1BD30-0AA0-Z Y10

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1050-1BD30-0AA0-Z\ Y10}$ 

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-1BD30-0AA0-Z Y10

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1050-1BD30-0AA0-Z Y10&lang=en

last modified: 1/27/2022 **C**