

ZBVJ65

Light block, Harmony XB5, Harmony XB4, blue for head Ø22 mm integral LED 12 V spring clamp terminals



Main

| | |
|-------------------------------|----------------------------|
| Range of Product | Harmony XB5 Harmony XB4 |
| Product or Component Type | Light block |
| Device short name | ZBV |
| Sale per indivisible quantity | 4 |
| Connections - terminals | Spring clamp terminals |
| Signalling type | Steady |
| Light source | Protected LED |
| Bulb base | Integral LED |
| Light block supply | Direct |
| Light source colour | Blue |
| [Us] rated supply voltage | 12 V AC/DC 50/60 Hz |

Complementary

| | |
|-----------------------------|---|
| Net Weight | 0.04 lb(US) (0.017 kg) |
| Supply voltage limits | 10...15 V DC 10.2...13.8 V AC |
| Current Consumption | 18 mA |
| Service life | 100000 h at rated voltage and 25 °C |
| Surge withstand | 1 kV IEC 61000-4-5 |
| Mounting of block | Front mounting |
| Electrical composition code | M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PF1 |

Environment

| | |
|---------------------------------------|---|
| Protective treatment | TH |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C) |
| IP degree of protection | IP20 IEC 60529 |
| Standards | EN/IEC 60947-5-4 EN/IEC 60947-5-5 UL 508 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C8201-5-1 JIS C8201-1 |
| Resistance to fast transients | 2 kV IEC 61000-4-4 |
| Resistance to electromagnetic fields | 9.14 V/m (10 V/m) IEC 61000-4-3 |

| | |
|---------------------------------------|--|
| Resistance to electrostatic discharge | 6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2 |
| Electromagnetic emission | Class B IEC 55011 |
| [Us] rated supply voltage | 12 V |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule | CS2 |
| GTIN | 3389119037488 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.52 oz (43 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 2.20 in (5.6 cm) |
| Package 1 width | 1.73 in (4.4 cm) |
| Package 1 Length | 2.13 in (5.4 cm) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 4 |
| Package 2 Weight | 8.61 oz (244 g) |
| Package 2 Height | 2.20 in (5.6 cm) |
| Package 2 width | 1.73 in (4.4 cm) |
| Package 2 Length | 2.13 in (5.4 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions

with ZB5AZ009 Fixing Collar



with ZB4BZ009 Fixing Collar

