


# UGT588

## Ultrasonic sensor

UGQ00800F1KG/US



- 1 LED echo
- 2 LED switching status
- 3 teach button



Product characteristics	
Electrical design	NPN
Output function	normally open / normally closed; (parameterisable + 1x current output)
Sensing range [mm]	60...800; (Target: 100 x 100 mm)
Housing	rectangular with M18 thread
Dimensions [mm]	53 x 20 x 37.7
Electrical data	
Operating voltage [V]	10...30 DC; ("supply class 2" to cULus)
Current consumption [mA]	< 35
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	< 0.3
Converter frequency [kHz]	230
Inputs / outputs	
Number of inputs and outputs	Number of digital outputs: 1; Number of analogue outputs: 1
Outputs	
Total number of outputs	2
Electrical design	NPN
Number of digital outputs	1
Output function	normally open / normally closed; (parameterisable + 1x current output)
Max. voltage drop switching output DC [V]	2.2
Permanent current rating of switching output DC [mA]	100
Switching frequency DC [Hz]	5

# UGT588



## Ultrasonic sensor

UGQ00800F1KG/US

Number of analogue outputs	1
Analogue current output [mA]	4...20
Max. load [ $\Omega$ ]	500
Short-circuit protection	yes
Overload protection	yes

Detection zone	
Sensing range [mm]	60...800; (Target: 100 x 100 mm)
Blind zone [mm]	60
Angle of aperture cylindrical [ $^{\circ}$ ]	15; ( $\pm 2$ )
Max. deviation from the 90° angle sensor/object [ $^{\circ}$ ]	$\pm 4$

Accuracy / deviations	
Temperature compensation	yes
Hysteresis [%]	< 1
Switch point drift [%]	-5...5
Linearity error of analogue output [%]	$\leq 1$
Repeatability	1 %
Resolution [mm]	3
Notes on the accuracy / deviation	The indicated values are reached after a warm-up time of min. 20 minutes

Response times	
Response time [ms]	< 450; (analogue output)

Operating conditions	
Ambient temperature [ $^{\circ}\text{C}$ ]	-20...70
Storage temperature [ $^{\circ}\text{C}$ ]	-30...80
Protection	IP 67

Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	3 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	3 V
	EN 55011	Class A
Vibration resistance	EN 60068-2-6 Fc	(10-55) Hz 1 mm amplitude, oscillation period 5 min., 30 min. per axis at resonance or 55 Hz
Shock resistance	EN 60068-2-27 Ea	30 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes
MTTF [years]		191
UL approval	Ta	-20...70 $^{\circ}\text{C}$
	power supply	Class 2
	File number UL	E174191

Mechanical data	
Weight [g]	99
Housing	rectangular with M18 thread
Dimensions [mm]	53 x 20 x 37.7

# UGT588



## Ultrasonic sensor

UGQ00800F1KG/US

Thread designation	M18 x 1
Materials	1.4542 (17-4 PH / 630); PBT; PA; epoxy glass ceramics
Tightening torque [Nm]	50

### Displays / operating elements

Display	switching status	1 x LED, yellow
	echo	1 x LED, green
Teach function	yes	

### Accessories


Items supplied	lock nuts: 1, stainless steel
----------------	-------------------------------

### Remarks


Remarks	operating voltage "supply class 2" according to cULus
Pack quantity	1 pcs.

### Electrical connection

Connector: 1 x M12; coding: A





### Connection





### Diagrams and graphs



- 1: distance
- 2: Detection zone
- 3: switch-on/switch-off graph
- 4: Target 100 x 100 mm
- 5: 50% of the target in the detection zone
- 6: switch point