



Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73038, blue, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, Key removal I

|   |                                    |
|---|------------------------------------|
| <b>product brand name</b>                                 | SIRIUS ACT                         |
| <b>product designation</b>                                | Key-operated switches              |
| <b>design of the product</b>                              | Actuating/signaling element        |
| <b>product type designation</b>                           | 3SU1                               |
| <b>product line</b>                                       | Metal, shiny, 22 mm                |
| <b>manufacturer's article number of included key</b>      | <a href="#">3SU1950-0FJ50-0AA0</a> |
| <b>Actuator</b>   |                                    |
| <b>principle of operation of the actuating element</b>    | latching, 90° (10:30 h/13:30 h)    |
| <b>product extension optional light source</b>            | No                                 |
| <b>color</b>  |                                    |
| • of the actuating element                                | blue                               |
| <b>material of the actuating element</b>                  | metal                              |
| <b>shape of the actuating element</b>                     | Key                                |
| <b>outer diameter of the actuating element</b>            | 29.5 mm                            |
| <b>number of switching positions</b>                      | 2                                  |
| <b>switch position for key distraction</b>                | I                                  |
| <b>actuating angle</b>                                    |                                    |
| • clockwise   | 90°                                |
| <b>lock make</b>  | O.M.R.                             |
| <b>key number</b>   | 73038                              |
| <b>Front ring</b>   |                                    |
| <b>product component front ring</b>                       | Yes                                |
| <b>design of the front ring</b>                           | Standard                           |
| <b>material of the front ring</b>                         | Metal, high gloss                  |
| <b>color of the front ring</b>                            | silver                             |
| <b>General technical data</b>                             |                                    |
| <b>protection class IP</b>                                | IP66, IP67, IP69(IP69K)            |
| • of the terminal   | IP20                               |
| <b>degree of protection NEMA rating</b>                   | 1, 2, 3, 3R, 4, 4X, 12, 13         |
| <b>shock resistance</b>                                   |                                    |
| • according to IEC 60068-2-27                             | sinusoidal half-wave 15g / 11 ms   |
| <b>vibration resistance</b>                               |                                    |
| • according to IEC 60068-2-6                              | 10 ... 500 Hz: 5g                  |
| <b>operating frequency maximum</b>                        | 1 800 1/h                          |
| <b>mechanical service life (switching cycles) typical</b> | 300 000                            |
| <b>reference code according to IEC 81346-2</b>            | S                                  |
| <b>Substance Prohibitance (Date)</b>                      | 10/01/2014                         |
| <b>Ambient conditions</b>                                 |                                    |
| <b>ambient temperature</b>                                |                                    |

- during operation
- during storage

-25 ... +70 °C

-40 ... +80 °C

environmental category during operation according to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

#### Installation/ mounting/ dimensions

|   |         |
|---|---------|
| height                                      | 29.5 mm |
| width                                       | 29.5 mm |
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 51.7 mm |
| installation width                          | 29.5 mm |
| installation depth                          | 25.4 mm |

#### Certificates/ approvals

General Product Approval

Declaration of Conformity



[Confirmation](#)



EG-Konf.



Test Certificates

Marine / Shipping

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



RINA

Marine / Shipping

other



RMRS

[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-4GF21-0AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-4GF21-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-4GF21-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-4GF21-0AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-4GF21-0AA0&lang=en)

last modified:

1/26/2022