

6

5

4

3

2

1


APPROVED: _____

DATE: _____ TITLE: _____

CUSTOM CABLE ASSEMBLIES ARE NON-CANCELLABLE/NON-RETURNABLE

Rev	AWO #	Description	Date	Appr
-		RELEASED	7/29/20	
A		UPDATE SPEC.	3/3/21	LH/RC

(Number of Conductors)	N	12P
(Pitch)	P	0.50±0.05
(Total Pitch)	Pt	5.50±0.07
(Total Length)	L	30.0±2.00
(Film Length)	IL	22.0±2.00
(Margin Width)	M	0.50±0.07
(Total Width)	W	6.50±0.07
(Strip Length)	S1	4.00±1.00
(Strip Length)	S2	4.00±1.00
(Stiffener)	B1	8.00±2.00
(Stiffener)	B2	8.00±2.00
(Slanting)	A1	≤0.30
(Slanting)	A2	≤0.30
(Terminal thickness)	t	0.30±0.03
(Thickness)	T	0.12±0.03



SPECIFICATIONS:

Material:
 Insulator: PET, color White.
 Support Tape: PET, color Blue.
 UL Style: AWM 2743, 105°C, 90V VW-1 Δ
 Plating:
 Conductor: Tin plated Copper Flat plated.
 Environmental:
 Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MILLIMETERS
 TOLERANCES: EXCEPT AS NOTED
 SEE CHART



909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

APPROVALS		DATE
DRAWN	AY	7/29/20
CHECKED	RC	7/29/20
APPROVED		

TITLE			FLAT FLEXIBLE CABLE, .020" [0.5MM] PITCH		
			SAME SIDE CONTACTS, TOTAL LENGTH 30.0MM		
SIZE	PART NO.	REV.			
X	CA-DK05-12-30.0-A-44-88	A			
REF:	S00187C	SCALE:	NTS	SHEET 1 OF 1	

6

5

4

3

2

1