

**MODEL:** CEP-2224 | **DESCRIPTION:** PIEZO BUZZER INDICATOR**FEATURES**

- through-hole pins
- 12 Vdc rating
- 3.4 kHz rated frequency
- low profile

**SPECIFICATIONS**

| parameter             | conditions/description  | min   | typ   | max   | units |
|-----------------------|-------------------------|-------|-------|-------|-------|
| rated voltage         |                         |       | 12    |       | Vdc   |
| operating voltage     |                         | 3     |       | 20    | Vdc   |
| current consumption   | at rated voltage        |       |       | 15    | mA    |
| rated frequency       |                         | 2,900 | 3,400 | 3,900 | Hz    |
| sound pressure level  | at 30 cm, rated voltage | 78    |       |       | dB    |
| dimensions            | ∅24.0 x 9.0             |       |       |       | mm    |
| weight                |                         |       |       | 1.2   | g     |
| material              | ABS PA-777D (black)     |       |       |       |       |
| terminal              | pin type (Sn plating)   |       |       |       |       |
| operating temperature |                         | -30   |       | 85    | °C    |
| storage temperature   |                         | -40   |       | 95    | °C    |
| RoHS                  | yes                     |       |       |       |       |

Notes: 1. All specifications measured at 5-35°C, humidity at 45-85%, under 86-106kPa pressure, unless otherwise noted.


**SOLDERABILITY**

| parameter                   | conditions/description | min | typ | max | units |
|-----------------------------|------------------------|-----|-----|-----|-------|
| hand soldering <sup>2</sup> | for maximum 2 seconds  | 330 |     | 380 | °C    |

Notes: 2. Not recommended for wave soldering

## MECHANICAL DRAWING


units: mm  
tolerance: ±0.5 mm



## PERFORMANCE CURVES


P: Voltage vs. Sound Pressure Level  
I: Voltage vs. Current Consumption

at 30cm




## PACKAGING

Inner Unit Size: 305 x 245 x 49 mm  
 Carton Size: 530 x 330 x 280 mm  
 Tray QTY: 125 pcs per tray  
 Inner Unit QTY: 250 pcs per unit  
 Carton QTY: 2,500 pcs per carton



|                |                          |
|----------------|--------------------------|
| Lot No.        | XXXXXXXXXX               |
| Model No.      | XXXXXXXXXX<br>XXXXXXXXXX |
| Quantity.      | XXXX Pcs                 |
| Date:          | DD MM YY                 |
| RoHs Compliant |                          |
| MADE IN CHINA  |                          |



## REVISION HISTORY

| rev. | description                  | date       |
|------|------------------------------|------------|
| 1.0  | initial release              | 09/19/2006 |
| 1.01 | applied new spec template    | 03/19/2019 |
| 1.02 | brand update                 | 10/11/2019 |
| 1.02 | logo, datasheet style update | 08/05/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[cuidevices.com](http://cuidevices.com)