




Figure similar

SIPLUS S7-1200 SM 1232 based on 6ES7222-1XF32-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, S7-1200, digital output SM 1222, 8 DQ, Relay changeover contact

| General information | |
|---|---|
| Product type designation | SM 1222, DQ 8x relay/2 A |
| Supply voltage | |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Input current | |
| from backplane bus 5 V DC, max. | 140 mA |
| Digital outputs | |
| <ul style="list-style-type: none"> from load voltage L+, max. | 16.7 mA/relay coil |
| Power loss | |
| Power loss, typ. | 5 W |
| Digital outputs | |
| Number of digital outputs | 8 |
| <ul style="list-style-type: none"> in groups of | 1 |
| Short-circuit protection | No; to be provided externally |
| Switching capacity of the outputs | |
| <ul style="list-style-type: none"> with resistive load, max. on lamp load, max. | 2 A 30 W with DC, 200 W with AC |
| Output voltage | |
| <ul style="list-style-type: none"> Rated value (DC) Rated value (AC) | 5 V DC to 30 V DC 5 V AC to 250 V AC |
| Output current | |
| <ul style="list-style-type: none"> for signal "1" permissible range, max. | 2 A |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> "0" to "1", max. "1" to "0", max. | 10 ms 10 ms |
| Total current of the outputs (per group) | |
| horizontal installation | |
| — up to 50 °C, max. | 2 A; Current per mass |
| Relay outputs | |
| <ul style="list-style-type: none"> Number of relay outputs Rated supply voltage of relay coil L+ (DC) Number of operating cycles, max. | 8 24 V mechanically 10 million, at rated load voltage 100 000 |
| Switching capacity of contacts | |
| <ul style="list-style-type: none"> with inductive load, max. on lamp load, max. with resistive load, max. | 2 A 30 W with DC, 200 W with AC 2 A |
| Cable length | |

| | |
|---|---|
| <ul style="list-style-type: none"> • shielded, max. | 500 m |
| <ul style="list-style-type: none"> • unshielded, max. | 150 m |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| <ul style="list-style-type: none"> • Diagnostic alarm | Yes |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> • for status of the outputs | Yes |
| <ul style="list-style-type: none"> • for maintenance | Yes |
| Potential separation | |
| Potential separation digital outputs | |
| <ul style="list-style-type: none"> • between the channels | Relays |
| <ul style="list-style-type: none"> • between the channels, in groups of | 1 |
| <ul style="list-style-type: none"> • between the channels and backplane bus | 1 500 V AC for 1 minute |
| Permissible potential difference | |
| between different circuits | 750 V AC for 1 minute |
| Degree and class of protection | |
| IP degree of protection | IP20 |
| Standards, approvals, certificates | |
| Marine approval | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • min. | -40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C |
| <ul style="list-style-type: none"> • max. | 70 °C; = Tmax; Tmax > +60 °C number of simultaneously activated outputs 4 (no adjacent points) for horizontal mounting position |
| <ul style="list-style-type: none"> • At cold restart, min. | -25 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> • min. | -40 °C |
| <ul style="list-style-type: none"> • max. | 70 °C |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> • Installation altitude above sea level, max. | 2 000 m |
| <ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC |
| Relative humidity | |
| <ul style="list-style-type: none"> • Operation at 25 °C without condensation, max. | 95 % |
| <ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |

| | |
|---|---|
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| <ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p> |
| connection method / header | |
| required front connector | Yes |
| Mechanics/material | |
| Enclosure material (front) <ul style="list-style-type: none"> • Plastic | Yes |
| Dimensions | |
| Width | 45 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 310 g |
| last modified: | 1/16/2021  |