

### product type designation



### W761-1 RJ45 (USA)

IWLAN Access Point, SCALANCE W761-1 RJ45, 1 radio, 1 R-SMA antenna port, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM German/English, 1x joint block; only for operation in the USA.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>with WLAN / maximum</li> <li>for Industrial Ethernet</li> </ul>	150 Mbit/s 10, 100 Mbit/s
transfer rate / for Industrial Ethernet	
<ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>	10 Mbit/s 100 Mbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> <li>for power supply</li> <li>for redundant voltage supply</li> </ul>	1 1 0
type of electrical connection	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> <li>for power supply</li> </ul>	RJ45 socket 3-pole screw terminal
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG</li> <li>KEY-PLUG</li> </ul>	No No
memory	
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG</li> <li>KEY-PLUG</li> </ul>	No No
interfaces / wireless	
number of radio cards / permanently installed	1
number of electrical connections / for external antenna(s)	1
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
consumed current	
<ul style="list-style-type: none"> <li>at DC / at 24 V / typical</li> </ul>	0.15 A
power loss [W]	
<ul style="list-style-type: none"> <li>at DC / at 24 V / typical</li> </ul>	3.6 W
supply voltage / 1	
<ul style="list-style-type: none"> <li>from terminal block</li> </ul>	19.2 V
supply voltage / 2	
<ul style="list-style-type: none"> <li>from terminal block</li> </ul>	28.8 V

ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	0 ... 55 °C -40 ... +85 °C -40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20
design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
<ul style="list-style-type: none"> <li>S7-300 rail mounting</li> <li>S7-1500 rail mounting</li> <li>35 mm top hat DIN rail mounting</li> <li>wall mounting</li> </ul>	No No Yes No
radio frequencies	
operating frequency	
<ul style="list-style-type: none"> <li>for WLAN in 2.4 GHz frequency band</li> <li>for WLAN in 5 GHz frequency band</li> </ul>	2.41 ... 2.48 GHz; depending on the country approvals 4.9 ... 5.8 GHz; depending on the country approvals
product features, product functions, product components / general	
product function / Access Point Mode	Yes
product function / client Mode	Yes
number of SSIDs	1
product function	
<ul style="list-style-type: none"> <li>iPCF Access Point</li> <li>iPCF client</li> <li>iPCF-MC Access Point</li> <li>iPCF-MC client</li> </ul>	No No No No
product function / iREF	No
product function / iPRP	No
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	4
product function	
<ul style="list-style-type: none"> <li>CLI</li> <li>web-based management</li> <li>MIB support</li> <li>TRAPs via email</li> <li>configuration with STEP 7</li> <li>configuration with STEP 7 in the TIA Portal</li> <li>operation with IWLAN controller</li> <li>operation with Enterasys WLAN controller</li> <li>forced roaming on IP down with IWLAN</li> <li>forced roaming on link down with IWLAN</li> <li>WDS</li> </ul>	Yes Yes Yes Yes Yes Yes No No Yes Yes Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>Address Resolution Protocol (ARP)</li> <li>ICMP</li> <li>Telnet</li> <li>HTTP</li> <li>HTTPS</li> </ul>	Yes Yes Yes Yes Yes

<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• LLDP</li> </ul>	Yes
identification & maintenance function	
<ul style="list-style-type: none"> <li>• I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• I&amp;M1 – higher level designation/location designation</li> </ul>	Yes
<b>product functions / diagnostics</b>	
product function	
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	No
<ul style="list-style-type: none"> <li>• link check</li> </ul>	No
<ul style="list-style-type: none"> <li>• connection monitoring IP-Alive</li> </ul>	No
<ul style="list-style-type: none"> <li>• localization via Aeroscout</li> </ul>	No
<ul style="list-style-type: none"> <li>• SysLog</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
<b>product functions / VLAN</b>	
product function	
<ul style="list-style-type: none"> <li>• function VLAN with IWLAN</li> </ul>	Yes
<b>product functions / DHCP</b>	
product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP server</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>	Yes
<b>product functions / redundancy</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• STP/RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RSTP</li> </ul>	Yes
<b>product functions / security</b>	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• management security, ACL-IP based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• NAT/NAPT</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• access protection according to IEEE802.11i</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• WPA/WPA2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TKIP/AES</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RADIUS</li> </ul>	Yes
<b>product functions / time</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SIMATIC time synchronization (SIMATIC Time)</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
certificate of suitability	
<ul style="list-style-type: none"> <li>• EC Declaration of Conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<ul style="list-style-type: none"> <li>• railway application in accordance with EN 50155</li> </ul>	No
<ul style="list-style-type: none"> <li>• railway application in accordance with EN 50121-4</li> </ul>	No

<ul style="list-style-type: none"> <li>• NEMA TS2</li> <li>• IEC 61375</li> <li>• IEC 61850-3</li> <li>• NEMA4X</li> <li>• Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af</li> <li>• Power-over-Ethernet according to IEEE802.3at for type 2</li> </ul>	No
	No
	No
	No
	No
	No
standard for wireless communication	
<ul style="list-style-type: none"> <li>• IEEE 802.11a</li> <li>• IEEE 802.11b</li> <li>• IEEE 802.11e</li> <li>• IEEE 802.11g</li> <li>• IEEE 802.11h</li> <li>• IEEE 802.11i</li> <li>• IEEE 802.11n</li> </ul>	Yes
	Yes
	Yes
	Yes
	Yes
	Yes
	Yes
wireless approval	You will find the current list of countries at: <a href="http://www.siemens.de/funkzulassungen">www.siemens.de/funkzulassungen</a>
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• DNV GL</li> <li>• Korean Register of Shipping (KRS)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>	No
	No
	No
	No
	No
	No
	No
	No
	No
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<b>accessories</b>	
accessories	24 V DC screw terminal included in scope of delivery
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>• to website: TIA Selection Tool</li> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to the website: IWLAN</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a> <a href="http://www.siemens.com/iwlan">http://www.siemens.com/iwlan</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)

last modified:

5/11/2022 