



Product: <u>1696A</u> ☑

Digital Audio Cable, 1 Pr #22, Str TC, Foil + Braid, PVC Jkt

Product Description

Digital Audio Cable, 1 Pair 22 AWG (7 x 30) Tinned Copper, Datalene® Insulation, Overall Beldfoil® Shield, 90% Tinned Copper Braid Shield, PVC jacket

Technical Specifications

Product Overview

Suitable A	applications:	ween audio equipment su	h as mic			
Constru	ction Details					
Conductor	r					
Element	Number of Element	Size Strandir	g Material			
Pair(s)	1 22	AWG 7x30	TC - Tinned Coppe	er		
Insulation						
Element	Material	Nom. Thickr	ess Nom. Insulation	n Diameter Color Code	Notes	
Pair(s)	PE - Polyethylene (Foam) 0.027 in (0.69	mm) 0.082 in (2.1 mr	n) Blue & White	HDPE	
Outer Shie	ald					
Shield Ty	pe Material	Coverage	Drainwire Type			
Таре	Bi-Laminate (Alum+P	oly) 100%	24 AWG (7x32) TC			
Braid	Tinned Copper (TC)	90%				
Outer Jack						
	Material Nom. Thickness Nom. Diameter					
	Material Nom. Inickness Nom. Diameter PVC - Polyvinyl Chloride 0.025 in (0.64 mm) 0.235 in (5.97 mm)					
Overall Ca	able Diameter (Nominal):	0.235 ir	(5.97 mm)			
	(. ,			

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	18.2 Ohm/1000ft	13 pF/ft (43 pF/m)	26 pF/ft (85 pF/m)	110 Ohm	76%	6 Amps per conductor @ 30°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating		
60°C	-30°C to +60°C		

Bend Radius

Stationary Min. Installation Min.

2.4 in (61 mm) 2.4 in (61 mm)					
Max. Pull Tension:	23.7 lbs (10.8 kg)				
Bulk Cable Weight:	31 lbs/1000ft				

Standards and Compliance

Indoor (Not Riser or Plenum), Indoor			
IEC 60332-1-2			
CPR Euroclass: Eca			
EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UKCA Mark			
China RoHS II (GB/T 26572-2011)			
AES/EBU			

Product Notes

Notes:	Cabling has two rod fillers for improved electrical performance.			
History				
Update and Revision:	Revision Number: 0.474 Revision Date: 01-20-2023			

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	
1696A B59250	Black, Matte	Reel	250 ft	612825121329	
1696A B59500	Black, Matte	Reel	500 ft	612825121336	
1696A B591000	Black, Matte	Reel	1,000 ft	612825121312	
1696A B59U1000	Black, Matte	Reel	1,000 ft	612825121305	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.