



Product: <u>1309A</u> ☑

Speaker Cable, 2 C #14 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 2 Conductor 14 AWG (105 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

Product Overview											
Suitable Applications: Speaker Cable; Direct Burial; Indoor/Outdoor Home Theater; In-Wall Speaker; Outdoor Speaker											
Construction Details											
Conductor											
Element Number of Element	t Size Stranding	Materia									
Conductor(s) 2	14 AWG 105x34	BC - Bare Copper (Hig	h Conductivity)								
Insulation											
Element Material Nom. Thickness Nom. Insulation Diameter Color Code											
Conductor(s) PE - Polyethylene 0.016 in (0.41 mm) 0.105 in (2.67 mm) Black, Red											
Outer Jacket											
Material Nom. Thickness Nom. Diameter											
PVC - Polyvinyl Chloride 0.027 in (0.69 mm) 0.264 in (6.71 mm)											
Overall Cable Diameter (Nominal):	0.264 in (6.71 mm)										
Electrical Characteristics											
Electricals											
Element Nom. Conductor D	CR Nom. Capacitance	e Cond-to-Cond Nom.	Velocity of Prop.	. Max. Current							
Conductor(s) 2.67 Ohm/1000ft	20.5 pF/ft (67.3 pF	/m) 66%		25 Amps per conductor @ 30°C							
Voltage											
UL Voltage Rating 300 V (CM, CL3)											
Mechanical Characteristics											
Temperature UL Temperature Operating											
OctomperatureOperating75°C-20°C To +75°C											
Bend Radius	_										
Stationary Min.Installation Min.2.6 in (66 mm)2.6 in (66 mm)	4										
Max. Pull Tension:	104 lbs (47.2 kg)										
Bulk Cable Weight:	Cable Weight: 42 lbs/1000ft										
Standards and Compliance	20			Standards and Compliance							

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor, Burial
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	СМ
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6100UE
Product Notes	

Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

History

Notes:

Update and Revision: Revision Number: 0.491 Revision Date: 04-14-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1309A 010U500	Black	UnReel	500 ft	612825111443
1309A 0101000	Black	Reel	1,000 ft	612825111450
1309A 006U500	Blue, Light	UnReel	500 ft	612825111412
1309A 008U500	Gray	UnReel	500 ft	612825111429
1309A 0081000	Gray	Reel	1,000 ft	612825111436
1309A N3UU500	Green, Mil	UnReel	500 ft	612825111405
1309A 1SLU500	White 1SL	UnReel	500 ft	612825111467
1309A 1SL1000	White 1SL	Reel	1,000 ft	612825111474

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.