## **SIEMENS**

## **Data sheet**



Twin pushbutton, 22 mm, round, plastic with metal front ring, green, red, pushbuttons, flat and raised, with laser labeling, upper case

| product brand name   | SIRIUS ACT                                 |
|--|--|
| product designation  | Twin pushbuttons                           |
| design of the product  | Actuating/signaling element                |
| product type designation   | 3SU1                                       |
| product line   | Plastic with metal front ring, matt, 22 mm |
| Enclosure  |  |
| number of command points   | 1  |
| Actuator   |  |
| design of the actuating element                                    | Flat/raised buttons                        |
| principle of operation of the actuating element                    | momentary contact type                     |
| product extension optional   |  |
| • light source   | No   |
| • contact module   | Yes  |
| color of the actuating element                                     | green / red                                |
| material of the actuating element                                  | plastic                                    |
| shape of the actuating element                                     | oval                                       |
| marking of the actuating element                                   | Any inscription, text in upper case        |
| Front ring   |  |
| product component front ring                                       | Yes  |
| design of the front ring   | Standard                                   |
| material of the front ring   | Metal, matt                                |
| color of the front ring  | sand gray                                  |
| General technical data   |  |
| protection class IP  | IP66, IP67, IP69(IP69K)                    |
| degree of protection NEMA rating                                   | 1, 2, 3, 3R, 4, 4X, 12, 13                 |
| shock resistance   |  |
| <ul><li>according to IEC 60068-2-27</li></ul>                      | sinusoidal half-wave 15g / 11 ms           |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B                        |
| vibration resistance   |  |
| <ul><li>according to IEC 60068-2-6</li></ul>                       | 10 500 Hz: 5g                              |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B                        |
| operating frequency maximum  | 3 600 1/h                                  |
| mechanical service life (switching cycles) typical                 | 2 000 000                                  |
| reference code according to IEC 81346-2                            | S  |
| Substance Prohibitance (Date)                                      | 10/01/2014                                 |
| Ambient conditions   |  |
| ambient temperature  |  |
| <ul> <li>during operation</li> </ul>                               | -25 +70 °C                                 |
| during storage   | -40 +80 °C                                 |

| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) |
|--|--|
| Installation/ mounting/ dimensions                             |  |
| height   | 57.9 mm  |
| width  | 29.9 mm  |
| shape of the installation opening                              | round  |
| mounting diameter  | 22.3 mm  |
| positive tolerance of installation diameter                    | 0.4 mm   |
| mounting height  | 18.7 mm  |
| installation width   | 29.9 mm  |
| installation depth   | 25.5 mm  |
| Certificates/ approvals  |  |
| Further information  |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1030-3BB42-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1030-3BB42-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1030-3BB42-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1030-3BB42-0AA0-Z Y11&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1030-3BB42-0AA0-Z Y11&lang=en</a>

last modified: 1/26/2022 🖸