SIEMENS

Data sheet

3SU1031-0BB50-0AA0-Z X90



Illuminated pushbutton, 22 mm, round, plastic with metal front ring, blue, pushbutton, raised momentary contact type, Z=100-unit packaging

product brand nameSIRIUS ACTproduct designationIlluminated pushbuttonsdesign of the productActuating/signaling elementproduct type designation3SU1product linePlastic with metal front ring, matt, 22 mmEnclosure1number of command points1ActuatorRaised button		
design of the product Actuating/signaling element product type designation 3SU1 product line Plastic with metal front ring, matt, 22 mm Enclosure 1 Actuator 1		
product type designation 3SU1 product line Plastic with metal front ring, matt, 22 mm Enclosure 1 Actuator 1		
product line Plastic with metal front ring, matt, 22 mm Enclosure 1 number of command points 1 Actuator 1		
Enclosure number of command points 1 Actuator		
number of command points 1 Actuator 1		
Actuator		
design of the actuating element Raised button		
principle of operation of the actuating element momentary contact type		
product extension optional		
light source Yes		
contact module Yes		
color of the actuating element blue		
material of the actuating element plastic		
shape of the actuating element round		
outer diameter of the actuating element 29.5 mm		
Front ring		
product component front ring Yes		
design of the front ring Standard		
material of the front ring Metal, matt		
color of the front ring sand gray		
General technical data		
protection class IP IP66, IP67, IP69(IP69K)		
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13		
shock resistance		
according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms		
for railway applications according to EN 61373 Category 1, Class B		
vibration resistance		
• according to IEC 60068-2-6 10 500 Hz: 5g		
for railway applications according to EN 61373 Category 1, Class B		
operating frequency maximum 3 600 1/h		
mechanical service life (switching cycles) typical 3 000 000		
reference code according to IEC 81346-2 S		
Substance Prohibitance (Date) 10/01/2014		
Ambient conditions		
ambient temperature		
• during operation -25 +70 °C		
• during storage -40 +80 °C		

environmental category during operation according to IEC 3M6, 3S2, 3B2, 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

Installation/ mounting/ dimensions		
height	29.5 mm	
width	29.5 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	16.2 mm	
installation width	29.5 mm	
installation depth	24.3 mm	
Certificates/ approvals		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1031-0BB50-0AA0-Z X90

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1031-0BB50-0AA0-Z X90

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1031-0BB50-0AA0-Z X90

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1031-0BB50-0AA0-Z X90&lang=en

last modified:

1/26/2022 🖸