## SIEMENS

## Data sheet

## 3SU1001-3BB42-0AA0-Z Y13



Illuminated twin pushbutton, 22 mm, round, plastic, green, red, pushbuttons, flat and raised, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

product brand name	SIRIUS ACT	
product designation	Twin pushbuttons	
design of the product	Actuating/signaling element	
product type designation	3SU1	
product line	Plastic, black, 22 mm	
Enclosure		
number of command points	1	
Actuator		
design of the actuating element	Flat/raised buttons, illuminated	
principle of operation of the actuating element	momentary contact type	
product extension optional		
light source	Yes	
contact module	Yes	
color of the actuating element	green / red	
material of the actuating element	plastic	
shape of the actuating element	oval	
marking of the actuating element	Customized labeling, graphical symbols acc. to ISO7000 and IEC60417	
Front ring		
product component front ring	Yes	
design of the front ring	Standard	
material of the front ring	plastic	
color of the front ring	black	
General technical data		
protection class IP	IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance		
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms	
<ul> <li>for railway applications acc. to DIN EN 61373</li> </ul>	Category 1, Class B	
vibration resistance		
<ul> <li>acc. to IEC 60068-2-6</li> </ul>	10 500 Hz: 5g	
<ul> <li>for railway applications acc. to DIN EN 61373</li> </ul>	Category 1, Class B	
operating frequency maximum	3 600 1/h	
mechanical service life (switching cycles) typical	2 000 000	
reference code acc. to IEC 81346-2	S	
Ambient conditions		
<ul> <li>ambient temperature during operation</li> </ul>	-25 +70 °C	
<ul> <li>ambient temperature during storage</li> </ul>	-40 +80 °C	
1		

environmental category during operation acc. to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10  $\dots$  95 %)

Installation/ mounting/ dimensions

height	57.9 mm
width	29.9 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	18.7 mm
installation width	29.9 mm
installation depth	25.5 mm
Certificates/ approvals	

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-3BB42-0AA0-Z Y13

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-3BB42-0AA0-Z Y13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-3BB42-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1001-3BB42-0AA0-Z Y13&lang=en

last modified:

1/5/2021 🖸